

CAPELLA LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	9.00 - 15.00
Luminous flux [lm]*:	750 - 1400

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

CAPELLA LED

GENERAL CARD

AVAILABLE VERSIONS




Click index >>, to see details


CAPELLA LED

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



CAPELLA LED



CAPELLA LED EDGE

Card creation date: 09 March 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 105/2018



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl