

# CAMEA LED LC

---

GENERAL CARD



## TECHNICAL PARAMETERS

---

<b>Nominal power [W]:</b>	9.00 - 16.00
<b>Luminous flux [lm]*:</b>	920 - 2150

## CHARACTERISTICS

---

Surface-mounted, round LED light fixture with high luminous flux, ingress protection class IP44, and an integrated energy-saving lights source LED. Base and ring made of UV-resistant plastic. A specially formed diffuser made of impact-resistant PC ensures the highest impact resistance of the fitting (IK10).

## APPLICATION

---

Luminaire suited for surface mounting on ceilings or walls, intended for indoor use (usable rooms, staircases, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms.

# CAMEA LED LC

---

GENERAL CARD

## AVAILABLE VERSIONS

---




[Click index >>, to see details](#)

# CAMEA LED LC

GENERAL CARD

## LUMINOUS INTENSITY DISTRIB. CURVE



CAMEA LED 9W 4000

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 397/2023; 73/2017