

FRAGA LED

GENERAL CARD



TECHNICAL PARAMETERS

Light source:	LED module
Ingress protection:	IP43/20
Nominal power [W]:	4.00; 6.00; 11.00; 15.00
Luminous flux [lm]*:	260 - 1150
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
Energy efficiency class:	F; G
Material of the body:	aluminium, PMMA
Colour of the body:	white
Diffuser material:	PMMA
Diffuser type:	PRM
Mounting version:	recessed
Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Dimensions (H/W/T/S) [mm]:	ø85/58; ø109/60; ø138/68;

CHARACTERISTICS

A downlight luminaire with narrow, 36° wide, light distribution angle and the light beam adjustable within +/-30°. Equipped with modern and energy-efficient COB LED light source. Its body made of aluminium and PMMA ensures optimum LED operating conditions and the diffuser made of highly transparent PMMA guarantees high luminous efficiency of the luminaire. Suitable for tool-free installation in plasterboard ceilings.

APPLICATION

Intended for indoor use in passageways and entry areas.

FRAGA LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

FRAGA LED 4W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
4	3000	260	PRM	ø85/58	G	>> 059209
4	4000	270	PRM	ø85/58	G	>> 059216

FRAGA LED 6W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
6	3000	360	PRM	ø85/58	G	>> 059223
6	4000	400	PRM	ø85/58	G	>> 059230

FRAGA LED 11W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
11	3000	640	PRM	ø109/60	G	>> 059247
11	4000	740	PRM	ø109/60	G	>> 059254


FRAGA LED 15W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
15	3000	1000	PRM	ø138/68	G	>> 059261
15	4000	1150	PRM	ø138/68	F	>> 059278

FRAGA LED

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



FRAGA LED 15W 4000K

FRAGA LED

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
059858	Round surface casing - white. 15W
059841	Round surface casing white NECTRA LED IP44 5W. NECTRA LED 5W. 7W, FRAGA LED 11W
060922	Round surface casing white NECTRA LED IP44 9W. NECTRA LED 7W, FRAGA 11W



Round surface casing - white.
15W (059858)



Round surface casing white NECTRA
LED IP44 5W. NECTRA LED 5W. 7W,
FRAGA LED 11W (059841)



Round surface casing white NECTRA
LED IP44 9W. NECTRA LED 7W,
FRAGA 11W (060922)

Card creation date: 14 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 352/2023; 94/2017