



## TECHNICAL PARAMETERS

---

**Luminous flux [lm]\*:** 2700 - 3850

## CHARACTERISTICS

---

Recessed mounted square LED luminaire for modular ceiling system with high total luminous flux (83 lm/W), made of powder coated white steel sheet, equipped with energy saving light sources LED GO! Highly uniform opal/prismatic diffuser, which enables low glare, mounting or electrical connection without removing the fitting. 3000K/4000K colour temperature, CRI>80, lightsource lifespan of 50 000h (L70B50) ta= 25°C.

## APPLICATION

---

Recessed luminaire for indoor application in offices or general use. Appropriate as the main light source even when the work requires eyesight concentration. Well suited for new applications as well as replacing conventional T8 & T5 with energy-saving solutions. Modular ceiling mounted (600x600 and 625x625)

# SENAR LED

---

GENERAL CARD

## AVAILABLE VERSIONS

---



Click index >>, to see details

Card creation date: 13 November 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 16/2014; 68/2014



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl