# LUNGO LED

GENERAL CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Light source:** | COB LED |
| **Ingress protection:** | IP20 |
| **Nominal power [W]:** | 10.00 |
| **Luminous flux [lm]*:** | 825; 860; 970 |
| **Colour temperature [K]:** | 3000; 4000 |
| **Color rendering index (Ra) >:** | 80 |
| **Energy efficiency class:** | E; F |
| **Material of the body:** | aluminium |
| **Colour of the body:** | black; black-gold; grey; white |
| **Diffuser material:** | PMMA |
| **Diffuser type:** | PRM |
| **Optics material:** | PMMA |
| **Optics:** | lens |
| **Mounting version:** | surface; suspended |
| **Working temperature [°C]:** | from -20 to +35 |
| **Supply voltage [V]:** | 220-240 |
| **Frequency [Hz]:** | 50 - 60; 50-60 |
| **Dimensions (H/W/T/S) [mm]:** | 60/145; 60/145/1500; 60/250; 60/250/1500; |
| **Warranty [years]:** | 2 |

## CHARACTERISTICS

The family of lungo luminaires will make each interior stylish and original. The option to combine different sizes and colours of luminaires allows creating original compositions which will be a decorative embellishment of rooms arranged in a modern way.

## APPLICATION

The luminaire is intended for indoor traffic zones included in table 5.1 of the EN12464 standard.

# LUNGO LED

GENERAL CARD

## AVAILABLE VERSIONS

Click index >>, to see details

LUNGO LED surface

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Beam angle [°] | Colour of the body | DIMM DALI | Dimensions (H/W/T/S) [mm] | Mounting version | Index |
|---|---|---|---|---|---|---|---|---|
| 10 | 3000 | 825 | 24 | grey | | 60/145 | surface | >> 645600 |
| 10 | 3000 | 825 | 24 | white | | 60/145 | surface | >> 645594 |
| 10 | 3000 | 825 | 24 | black-gold | | 60/145 | surface | >> 645587 |
| 10 | 3000 | 825 | 24 | black | | 60/145 | surface | >> 645570 |
| 10 | 3000 | 825 | 50 | grey | | 60/145 | surface | >> 645259 |
| 10 | 3000 | 825 | 50 | white | | 60/145 | surface | >> 645211 |
| 10 | 3000 | 825 | 50 | black-gold | | 60/145 | surface | >> 645228 |
| 10 | 3000 | 860 | 50 | black | | 60/145 | surface | >> 645242 |
| 10 | 3000 | 825 | 24 | grey | | 60/250 | surface | >> 645563 |
| 10 | 3000 | 825 | 24 | white | | 60/250 | surface | >> 645556 |
| 10 | 3000 | 825 | 24 | black-gold | | 60/250 | surface | >> 645549 |
| 10 | 3000 | 825 | 24 | black | | 60/250 | surface | >> 645532 |
| 10 | 3000 | 825 | 50 | grey | | 60/250 | surface | >> 645334 |
| 10 | 3000 | 825 | 50 | white | | 60/250 | surface | >> 645303 |
| 10 | 3000 | 825 | 50 | black-gold | | 60/250 | surface | >> 645310 |
| 10 | 3000 | 825 | 50 | black | | 60/250 | surface | >> 645327 |

LUNGO LED suspended

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Beam angle [°] | Colour of the body | DIMM DALI | Dimensions (H/W/T/S) [mm] | Mounting version | Index |
|---|---|---|---|---|---|---|---|---|
| 10 | 3000 | 825 | 24 | grey | | 60/145/1500 | suspended | >> 645631 |
| 10 | 3000 | 825 | 24 | white | | 60/145/1500 | suspended | >> 645617 |
| 10 | 3000 | 825 | 24 | black-gold | | 60/145/1500 | suspended | >> 645624 |
| 10 | 3000 | 825 | 24 | black | | 60/145/1500 | suspended | >> 645860 |
| 10 | 3000 | 825 | 50 | grey | | 60/145/1500 | suspended | >> 645297 |
| 10 | 3000 | 825 | 50 | white | | 60/145/1500 | suspended | >> 645266 |
| 10 | 3000 | 825 | 50 | black-gold | | 60/145/1500 | suspended | >> 645273 |
| 10 | 3000 | 825 | 50 | black | | 60/145/1500 | suspended | >> 645280 |
| 10 | 3000 | 825 | 24 | grey | | 60/250/1500 | suspended | >> 645679 |
| 10 | 3000 | 825 | 24 | white | | 60/250/1500 | suspended | >> 645655 |
| 10 | 3000 | 825 | 24 | black-gold | | 60/250/1500 | suspended | >> 645662 |
| 10 | 3000 | 825 | 24 | black | | 60/250/1500 | suspended | >> 645648 |
| 10 | 3000 | 825 | 50 | grey | | 60/250/1500 | suspended | >> 645853 |
| 10 | 3000 | 825 | 50 | white | | 60/250/1500 | suspended | >> 645341 |

# LUNGO LED


GENERAL CARD

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Beam angle [°] | Colour of the body | DIMM DALI | Dimensions (H/W/T/S) [mm] | Mounting version | Index |
|---|---|---|---|---|---|---|---|---|
| 10 | 3000 | 825 | 50 | black-gold | | 60/250/1500 | suspended | >> 645358 |
| 10 | 3000 | 825 | 50 | black | | 60/250/1500 | suspended | >> 645365 |
| 10 | 4000 | 970 | 50 | black | yes | 60/250/1500 | suspended | >> 645891 |


# LUNGO LED

GENERAL CARD

## LUMINOUS INTENSITY DISTRIB. CURVE



LUNGO 825lm 24D 250mm
ALUMINIUM 830 (10W)



LUNGO 825lm 50D 145mm
ALUMINIUM 830 (10W)

Card creation date: 03 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 161/2019; 229/2023

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl