

# TRIPACT LED P

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP40/20
<b>Nominal power [W]:</b>	24.00 - 60.00
<b>Luminous flux [lm]*:</b>	2300 - 6000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	E; F
<b>Material of the body:</b>	ABS
<b>Diffuser material:</b>	PMMA
<b>Diffuser type:</b>	OPAL
<b>Mounting version:</b>	recessed
<b>Dimensions (H/W/T/S) [mm]:</b>	595/595/93;
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

TRIPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.

# TRIPACT LED P

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### TRIPACT LED P 24W

Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Energy efficiency class	Index
3000	2300	OPAL		F	<a href="#">&gt;&gt; 658006</a>
4000	2500	OPAL		E	<a href="#">&gt;&gt; 658013</a>
3000	2300	OPAL	yes	F	<a href="#">&gt;&gt; 658167</a>
4000	2500	OPAL	yes	E	<a href="#">&gt;&gt; 658174</a>

### TRIPACT LED P 42W

Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Energy efficiency class	Index
3000	3750	OPAL		F	<a href="#">&gt;&gt; 658020</a>
4000	4050	OPAL		E	<a href="#">&gt;&gt; 658037</a>
3000	3750	OPAL	yes	F	<a href="#">&gt;&gt; 658181</a>
4000	4050	OPAL	yes	E	<a href="#">&gt;&gt; 658198</a>

### TRIPACT LED P 60W

Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Energy efficiency class	Index
3000	5300	OPAL		F	<a href="#">&gt;&gt; 658044</a>
4000	6000	OPAL		F	<a href="#">&gt;&gt; 658051</a>
3000	5300	OPAL	yes	F	<a href="#">&gt;&gt; 658204</a>
4000	6000	OPAL	yes	F	<a href="#">&gt;&gt; 658211</a>

# TRIPACT LED P


GENERAL CARD

## ACCESSORIES AVAILABLE

index	Name
<a href="#">999543</a>	Plasterboard recessing kit 630x630 white (steel version)
<a href="#">658372</a>	Diffuser TRIPACT



Plasterboard recessing kit 630x630 white (steel version) (999543)



Diffuser TRIPACT (658372)

Card creation date: 01 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 251/2023