

MADERA ALTUS LED EVO

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP41
Nominal power [W]:	50.00; 88.00
Luminous flux [lm]*:	4650 - 8700
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	F
Electrical protection class:	II
Colour of the body:	black; grey; white
Dimensions (H/W/T/S) [mm]:	900/900/120;
Warranty [years]:	2

CHARACTERISTICS

Suspended, square LED fitting with very high luminous flux, made of steel sheet, powder-coated grey, white, black. equipped with energy-saving light source LED. Opal PMMA diffuser ensures even light distribution and no glare effect.

APPLICATION

Suspended luminaire intended for indoor use in offices or common rooms. Suitable as a general light source in representative rooms.

MADERA ALTUS LED EVO

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

MADERA ALTUS LED EVO 50W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Colour of the body	Energy efficiency class	Index
50	3000	4650	white	F	>> 703836
50	4000	5050	white	F	>> 703805
50	3000	4650	black	F	>> 703850
50	4000	5050	black	F	>> 703829
50	3000	4650	grey	F	>> 703843
50	4000	5050	grey	F	>> 703812

MADERA ALTUS LED EVO 88W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Colour of the body	Energy efficiency class	Index
88	3000	8000	white	F	>> 703898
88	4000	8700	white	F	>> 703867
88	3000	8000	black	F	>> 703911
88	4000	8700	black	F	>> 703881
88	3000	8000	grey	F	>> 703904
88	4000	8700	grey	F	>> 703874

Card creation date: 27 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 170/2018; 225/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl