

CORPACT LED

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|---|---------------|
| Ingress protection: | IP40/20 |
| Nominal power [W]: | 24.00 - 60.00 |
| Luminous flux [lm]*: | 2300 - 6000 |
| Color rendering index (Ra) >: | 80 |
| SDCM: | 3 |
| Energy efficiency class: | E; F |
| Material of the body: | ABS |
| Diffuser material: | PMMA |
| Diffuser type: | OPAL |
| Mounting version: | recessed |
| Dimensions (H/W/T/S) [mm]: | 595/595/93; |

CHARACTERISTICS

CORPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.

CORPACT LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

CORPACT LED 24W

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | DIMM DALI | Energy efficiency class | Index |
|-------------------|------------------------|---------------------|---------------|-----------|-------------------------|---------------------------------|
| 24 | 3000 | 2300 | OPAL | | F | >> 658594 |
| 24 | 4000 | 2500 | OPAL | | E | >> 658600 |
| 24 | 3000 | 2300 | OPAL | yes | F | >> 658655 |
| 24 | 4000 | 2500 | OPAL | yes | E | >> 658662 |

CORPACT LED 42W

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | DIMM DALI | Energy efficiency class | Index |
|-------------------|------------------------|---------------------|---------------|-----------|-------------------------|---------------------------------|
| 42 | 3000 | 3750 | OPAL | | F | >> 658617 |
| 42 | 4000 | 4050 | OPAL | | E | >> 658624 |
| 42 | 3000 | 3750 | OPAL | yes | F | >> 658679 |
| 42 | 4000 | 4050 | OPAL | yes | E | >> 658686 |

CORPACT LED 60W


| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | DIMM DALI | Energy efficiency class | Index |
|-------------------|------------------------|---------------------|---------------|-----------|-------------------------|---------------------------------|
| 60 | 3000 | 5300 | OPAL | | F | >> 658631 |
| 60 | 4000 | 6000 | OPAL | | F | >> 658648 |
| 60 | 3000 | 5300 | OPAL | yes | F | >> 658693 |
| 60 | 4000 | 6000 | OPAL | yes | F | >> 658709 |

CORPACT LED

GENERAL CARD

ACCESSORIES AVAILABLE

| index | Name |
|------------------------|--------------------------------|
| 374845 | Frame adapter KG 635x635 WHITE |



Frame adapter KG 635x635
WHITE (374845)

Card creation date: 08 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 250/2023; 27/2019