

# SOLPACT LED

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP40/20
<b>Nominal power [W]:</b>	24.00 - 60.00
<b>Luminous flux [lm]*:</b>	2300 - 6000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>SDCM:</b>	3
<b>Energy efficiency class:</b>	E; F
<b>Material of the body:</b>	ABS
<b>Diffuser material:</b>	PMMA
<b>Diffuser type:</b>	OPAL
<b>Mounting version:</b>	recessed
<b>Dimensions (H/W/T/S) [mm]:</b>	595/595/87;
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

SOLPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.

# SOLPACT LED

## GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### SOLPACT LED 24W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Electrical protection class	Energy efficiency class	Index
24	3000	2300	OPAL		II	F	<a href="#">&gt;&gt; 658389</a>
24	4000	2500	OPAL		II	E	<a href="#">&gt;&gt; 658396</a>
24	3000	2300	OPAL	yes	I	F	<a href="#">&gt;&gt; 658440</a>
24	4000	2500	OPAL	yes	I	E	<a href="#">&gt;&gt; 658457</a>

### SOLPACT LED 42W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Electrical protection class	Energy efficiency class	Index
42	3000	3750	OPAL		II	F	<a href="#">&gt;&gt; 658402</a>
42	4000	4050	OPAL		II	E	<a href="#">&gt;&gt; 658419</a>
42	3000	3750	OPAL	yes	I	F	<a href="#">&gt;&gt; 658464</a>
42	4000	4050	OPAL	yes	I	E	<a href="#">&gt;&gt; 658471</a>

### SOLPACT LED 60W


Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Electrical protection class	Energy efficiency class	Index
60	3000	5300	OPAL		I	F	<a href="#">&gt;&gt; 658426</a>
60	4000	6000	OPAL		I	F	<a href="#">&gt;&gt; 658433</a>
60	3000	5300	OPAL	yes	I	F	<a href="#">&gt;&gt; 658488</a>
60	4000	6000	OPAL	yes	I	F	<a href="#">&gt;&gt; 658495</a>

# SOLPACT LED

GENERAL CARD

## ACCESSORIES AVAILABLE

index	Name
<a href="#">374845</a>	Frame adapter KG 635x635 WHITE



Frame adapter KG 635x635  
WHITE (374845)

Card creation date: 08 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 252/2023