

SOLPACT LED

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP40/20
Nominal power [W]:	24.00 - 60.00
Luminous flux [lm]*:	2300 - 6000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	E; F
Material of the body:	ABS
Diffuser material:	PMMA
Diffuser type:	OPAL
Mounting version:	recessed
Dimensions (H/W/T/S) [mm]:	595/595/87;
Warranty [years]:	5

CHARACTERISTICS

SOLPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.

SOLPACT LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

SOLPACT LED 24W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Electrical protection class	Energy efficiency class	Index
24	3000	2300	OPAL		II	F	>> 658389
24	4000	2500	OPAL		II	E	>> 658396
24	3000	2300	OPAL	yes	I	F	>> 658440
24	4000	2500	OPAL	yes	I	E	>> 658457

SOLPACT LED 42W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Electrical protection class	Energy efficiency class	Index
42	3000	3750	OPAL		II	F	>> 658402
42	4000	4050	OPAL		II	E	>> 658419
42	3000	3750	OPAL	yes	I	F	>> 658464
42	4000	4050	OPAL	yes	I	E	>> 658471

SOLPACT LED 60W


Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Electrical protection class	Energy efficiency class	Index
60	3000	5300	OPAL		I	F	>> 658426
60	4000	6000	OPAL		I	F	>> 658433
60	3000	5300	OPAL	yes	I	F	>> 658488
60	4000	6000	OPAL	yes	I	F	>> 658495

SOLPACT LED

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
	Plasterboard recessing kit 630x630 white (steel version)



Plasterboard recessing kit 630x630
white (steel version) (999543)

Card creation date: 02 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 252/2023