

ROUND LED

GENERAL CARD



TECHNICAL PARAMETERS

Luminous flux [lm]*: 450 - 640

CHARACTERISTICS

Surface mounted, round LED luminaire with an integrated, energy-saving LED GO! panel with high luminous efficacy and ingress protection of IP44. The base is available in white, black and gray. It was made of polypropylene and the diffuser is made of prismatic glass. The luminaire is available with a presence detector (PIR).

APPLICATION

Round, surface mounted luminaire for mounting on ceilings and walls; intended for indoor use (rooms with high humidity, passageways and staircases, sewers and basements) as well as outdoor use (industrial facade lighting, parking lots).

ROUND LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Card creation date:13 September 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric andelectronic waste equipment regulations (WEEE).



Certificate CE - Nr: 16/2018



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl