# **SPECTO LED EVO**

**GENERAL CARD** 





### **TECHNICAL PARAMETERS**

IP40

Impact resistance: IK02

**Nominal power [W]:** 15.00 - 15.00

**Luminous flux [lm]\*:** 1820 - 1950

Colour temperature [K]: 3000; 4000

Color rendering index (Ra) >: 80

SDCM: 3

Energy efficiency class:

Material of the body: steel

**Diffuser material:** PMMA

Diffuser type: PRM MAT

**Mounting version:** surface

**Dimensions (H/W/T/S) [mm]:** 595/45/84;

Warranty [years]: 5

### **CHARACTERISTICS**

Surface ceiling or wall mounted, high performance LED luminaire with compact space saving construction. Equipped with energy saving light sources LED. Powderpainted steel base, special multilayer prismatic diffuser combining high UV resistance PMMA cover and polypropylene optic system or single layer high UV resistance opal PMMA diffuser.

### **APPLICATION**

Multi-purpose LED luminaire designed for indoor application for illuminating public use areas and corridors (administration buildings, schools and universities, health care buildings) Especially recommended for small space application or as complementary lighting. It is appropriate for new applications as well as replacing conventional T8 & T5 fittings on energy saving LED solutions. Fitting construction adapted for surface mounting (ceiling or wall) using included accessory installation kit.



# **SPECTO LED EVO**

**GENERAL CARD** 

## **AVAILABLE VERSIONS**



#### SPECTO LED EVO 1


Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
15	3000	1820	PRM MAT	595/45/84	E	>> 342974
15	4000	1950	PRM MAT	595/45/84	Е	>> 342950




# **SPECTO LED EVO**

**GENERAL CARD** 

#### **LUMINOUS INTENSITY DISTRIB. CURVE**





SPECTO LED EVO PRM

SPECTO LED EVO PRM MAT

Card creation date: 19 May 2025

 $The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute and (a) a constitute and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance$ 

