

SPECTO LED EVO

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP40
Impact resistance:	IK02
Nominal power [W]:	15.00 - 36.00
Luminous flux [lm]*:	1820 - 4850
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	D; E; F
Material of the body:	steel
Diffuser material:	PMMA
Diffuser type:	PRM; PRM MAT
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	900/45/84; 1200/45/84; 1500/45/84; 595/45/84;
Warranty [years]:	5

CHARACTERISTICS

Surface ceiling or wall mounted, high performance LED luminaire with compact space saving construction. Equipped with energy saving light sources LED. Powderpainted steel base, special multilayer prismatic diffuser combining high UV resistance PMMA cover and polypropylene optic system or single layer high UV resistance opal PMMA diffuser.

APPLICATION

Multi-purpose LED luminaire designed for indoor application for illuminating public use areas and corridors (administration buildings, schools and universities, health care buildings) Especially recommended for small space application or as complementary lighting. It is appropriate for new applications as well as replacing conventional T8 & T5 fittings on energy saving LED solutions. Fitting construction adapted for surface mounting (ceiling or wall) using included accessory installation kit.

SPECTO LED EVO

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

SPECTO LED EVO 1

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
15	3000	1820	PRM MAT	595/45/84	E	>> 342974
15	4000	1950	PRM MAT	595/45/84	E	>> 342950

SPECTO LED EVO 2

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
22	3000	1950	PRM MAT	900/45/84	F	>> 636516
22	4000	2700	PRM MAT	900/45/84	E	>> 636431

SPECTO LED EVO 3

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
29	4000	2800	PRM MAT	1200/45/84	F	>> 636455


SPECTO LED EVO 4

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
36	3000	3850	PRM	1500/45/84	E	>> 636547
36	4000	4850	PRM MAT	1500/45/84	D	>> 636479


SPECTO LED EVO

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



SPECTO LED EVO PRM



SPECTO LED EVO PRM MAT

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 337/2023; 79/2017



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl