CAPELLA LED PLUS Z

GENERAL CARD





| Light source: | LED module |
|----------------------------|---------------|
| Ingress protection: | IP20 |
| Nominal power [W]: | 11.00; 15.00 |
| Luminous flux [lm]*: | 950 - 1650 |
| Colour temperature [K]: | 3000; 4000 |
| SDCM: | ≤3 |
| Energy efficiency class: | E; F |
| Material of the body: | ABS |
| Diffuser material: | PC |
| Diffuser type: | OPAL |
| Optics material: | PMMA |
| Optics: | lens |
| Mounting version: | suspended |
| Dimensions (H/W/T/S) [mm]: | 320/177/2200; |
| | |

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

Versions available on request:

- any RAL colour of the body,
- any RAL colour of the suspension system,
- selected colours of the material of the cable.

Next versions (available soon):

- IoT (adapted for integration with additional control systems).

APPLICATION

Suspended luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.



CAPELLA LED PLUS Z

GENERAL CARD

AVAILABLE VERSIONS

Click index \gg , to see details

CAPELLA LED PLUS Z

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Energy efficiency class | Index |
|-------------------|------------------------|---------------------|---------------|-------------------------|------------------------|
| 11 | 3000 | 1040 | OPAL | F | <u>>> 951305</u> |
| 11 | 4000 | 1120 | OPAL | E | <u>>> 951220</u> |
| 15 | 3000 | 1550 | OPAL | E | <u>>> 951312</u> |
| 15 | 4000 | 1650 | OPAL | E | <u>>> 951237</u> |

CAPELLA LED PLUS Z EDGE


| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Energy efficiency class | Index |
|-------------------|------------------------|---------------------|---------------|-------------------------|------------------------|
| 11 | 3000 | 950 | OPAL | F | <u>>> 951329</u> |
| 11 | 4000 | 1020 | OPAL | F | <u>>> 951244</u> |
| 15 | 3000 | 1400 | OPAL | F | <u>>> 951336</u> |
| 15 | 4000 | 1500 | OPAL | Е | <u>>> 951251</u> |




CAPELLA LED PLUS Z

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE





CAPELLA LED PLUS

CAPELLA LED PLUS EDGE

Card creation date: 13 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

Certificate CE - Nr: 162/2018

This product is a subject to electric and electronic waste equipment regulations (WEEE).

