

# OVAL LED EVO

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP44
<b>Impact resistance:</b>	IK06
<b>Nominal power [W]:</b>	5.00
<b>Luminous flux [lm]*:</b>	430 - 620
<b>Colour temperature [K]:</b>	3000; 4000
<b>SDCM:</b>	3; 4
<b>Energy efficiency class:</b>	E; F; G
<b>Material of the body:</b>	PP
<b>Diffuser material:</b>	PC; glass
<b>Diffuser type:</b>	OPAL; PRM
<b>Mounting version:</b>	surface
<b>Dimensions (H/W/T/S) [mm]:</b>	170/125/115; 170/125/110;

## CHARACTERISTICS

Surface-mounted, LED luminaire, with an integrated energy-efficient LED panel that provides high luminous efficacy and high ingress protection class of IP44 (wall assembly) and IP40 (ceiling assembly). The base is made of polypropylene and the diffuser is made of glass or polycarbonate. Characteristics: color temperature 3000K, 4000K; CRI> 80; durability of LED panels 50,000 hours (L70B50)  $t_a = 25^\circ \text{C}$

## APPLICATION

Surface mounted luminaire with plastic or metal grid for mounting on ceilings and walls; intended for indoor use (rooms with high humidity, passageways and staircases, sewers and basements) as well as outdoor use (industrial facade lighting, parking lots).

# OVAL LED EVO

## GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### OVAL LED EVO metal grid

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	Index
5	4000	620	PRM	white	<a href="#">&gt;&gt; 911071</a>
5	3000	530	PRM	gray	<a href="#">&gt;&gt; 911101</a>

### OVAL LED EVO metal, demountable grid

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	Index
5	3000	530	PRM	gray	<a href="#">&gt;&gt; 911200</a>
5	4000	580	PRM	gray	<a href="#">&gt;&gt; 911217</a>
5	4000	470	OPAL	gray	<a href="#">&gt;&gt; 911392</a>
5	3000	430	OPAL	gray	<a href="#">&gt;&gt; 911385</a>

### OVAL LED EVO plastic grid

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	Index
5	3000	540	PRM	gray	<a href="#">&gt;&gt; 911262</a>
5	4000	480	OPAL	gray	<a href="#">&gt;&gt; 911453</a>
5	4000	590	PRM	gray	<a href="#">&gt;&gt; 911279</a>
5	3000	440	OPAL	gray	<a href="#">&gt;&gt; 911446</a>

Card creation date: 19 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 183/2018; 402/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl