GENERAL CARD





TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W]:	15.00
Luminous flux [lm]*:	1550 - 1550
Colour temperature [K]:	4000

SDCM: 3

Energy efficiency class:

Material of the body: aluminium

Diffuser type: OPAL

Mounting version: surface

Dimensions (H/W/T/S) [mm]: Ø306/90;

CHARACTERISTICS

Surface-mounted, round LED fitting with increased ingress protection class IP65 and integrated energy-saving light source LED. Body and base made of high-pressure cast aluminum and powder coated silver or graphite. A specially formed diffuser made of impact-resistant PC ensures the highest possible impact resistance of the fitting (IK10). Color temperature 3000K/4000K, CRI>80, lifespan of LED 50 000h (L70B50) ta= 25 °C.

APPLICATION

Surface mounted luminaire intended for indoor or outdoor use. Suitable as a general light source in representative rooms and passageways. Very good mechanical parameters (increased ingress protection class IP65 and impact resistance IK10) allow this fitting to be used for facade applications.



TEO LED

GENERAL CARD

AVAILABLE VERSIONS



TEO LED 15W


Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	Energy efficiency class	Index
15	4000	1550	OPAL	graphite	F	<u>>> 191961</u>



TEO LED

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



TEO LED

Card creation date: 24 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

