

# DOBLO LED

## GENERAL CARD



### TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Impact resistance:</b>	IK07
<b>Nominal power [W]:</b>	36.00; 50.00
<b>Luminous flux [lm]*:</b>	3550 - 5350
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	E; F
<b>Material of the body:</b>	powder coated steel
<b>Diffuser material:</b>	PS
<b>Diffuser type:</b>	OPAL
<b>Mounting version:</b>	suspended
<b>Dimensions (H/W/T/S) [mm]:</b>	1180/200/52;

### CHARACTERISTICS

Decorative lighting fitting with the effect of indirect light constituting 30% of the total light output of the luminaire. It was made of powder-coated sheet steel and equipped with an economical LED panel. Specification: color temperature: 3000K/4000K; CRI>80; LED panels lifespan 50 000h (L70B50) for ta=25°C. DIMM/DALI options available on request.

### APPLICATION

A versatile indoor luminaire designed for office rooms and areas of general public use. It is perfect for representational spaces.

# DOBLO LED

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### DOBLO LED 36W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Energy efficiency class	Index
36	3000	3550	OPAL	white		F	<a href="#">&gt;&gt; 094002</a>
36	4000	3850	OPAL	white		E	<a href="#">&gt;&gt; 094019</a>
36	3000	3550	OPAL	white	yes	F	<a href="#">&gt;&gt; 094088</a>
36	4000	3850	OPAL	white	yes	E	<a href="#">&gt;&gt; 094095</a>
36	4000	3850	OPAL	grey		E	<a href="#">&gt;&gt; 094057</a>
36	3000	3550	OPAL	grey		F	<a href="#">&gt;&gt; 094040</a>
36	3000	3550	OPAL	grey	yes	F	<a href="#">&gt;&gt; 094125</a>
36	4000	3850	OPAL	grey	yes	E	<a href="#">&gt;&gt; 094132</a>


### DOBLO LED 50W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Energy efficiency class	Index
50	3000	4950	OPAL	white		F	<a href="#">&gt;&gt; 094026</a>
50	4000	5350	OPAL	white		E	<a href="#">&gt;&gt; 094033</a>
50	3000	4950	OPAL	white	yes	F	<a href="#">&gt;&gt; 094101</a>
50	4000	5350	OPAL	white	yes	E	<a href="#">&gt;&gt; 094118</a>
50	3000	4950	OPAL	grey		F	<a href="#">&gt;&gt; 094064</a>
50	4000	5350	OPAL	grey		E	<a href="#">&gt;&gt; 094071</a>
50	3000	4950	OPAL	grey	yes	F	<a href="#">&gt;&gt; 094149</a>
50	4000	5350	OPAL	grey	yes	E	<a href="#">&gt;&gt; 094156</a>

# DOBLO LED

GENERAL CARD

## LUMINOUS INTENSITY DISTRIB. CURVE



DOBLO LED

Card creation date: 14 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 371/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl