



TECHNICAL PARAMETERS

Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	9.00 - 17.00
Luminous flux [lm]*:	1150 - 2200
Colour temperature [K]:	3000; 4000
SDCM:	≤ 3; ≤ 5
Energy efficiency class:	E; F
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	OPAL
Optics material:	PC
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	ø280/72;
Warranty [years]:	5

CHARACTERISTICS

The latest version of the popular plafond - even better performance, same proven quality.

Surface-mounted, round LED light fitting with a luminous flux of 87 lm/W, ingress protection class IP54 and an integrated energy-saving light source LED. White base; diffuser made of impact-resistant PC provides even light distribution and ensures a high impact resistance class (IK10).

APPLICATION

Surface mounted fitting intended for indoor use in representative rooms and passageways (large conference halls, hotel corridors, studies). Designed for mounting on ceilings and walls. Wide range of diameters and two diffuser versions allow for the same fitting to be used in rooms with different parameters. Well suited to be used as a basic or general interior light source.

GAMMA LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

GAMMA LED 9W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	PIR	Index
9	3000	1150	OPAL			>> 191213
9	3000	1150	OPAL	yes		>> 191275
9	4000	1200	OPAL			>> 191084
9	4000	1200	OPAL	yes		>> 191251

GAMMA LED 12W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	PIR	Index
12	3000	1500	OPAL			>> 191220
12	3000	1500	OPAL	yes		>> 191282
12	4000	1600	OPAL			>> 191091
12	4000	1600	OPAL	yes		>> 191268

GAMMA LED 13W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	PIR	Index
13	4000	1500	OPAL		yes	>> 191183


GAMMA LED 17W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	PIR	Index
17	3000	2100	OPAL			>> 191237
17	3000	2100	OPAL	yes		>> 191299
17	4000	2200	OPAL			>> 191060
17	4000	2200	OPAL	yes		>> 191046

GAMMA LED

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE




GAMMA LED

GAMMA LED

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
WSE0005	RC MOS MR004 IoT programming remote control



RC MOS MR004 IoT programming
remote control (WSE0005)

Card creation date: 10 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 102/2021; 166/2020; 392/2023; 43/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl