

GAMMA LED BASIC

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	8.00 - 13.00
Luminous flux [lm]*:	800 - 1500
Colour temperature [K]:	3000; 4000
SDCM:	≤ 3; ≤ 5
Energy efficiency class:	E; F
Material of the body:	PC; PP
Diffuser material:	PC
Diffuser type:	OPAL
Optics material:	PC
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	ø220/72; ø280/72;
Warranty [years]:	3

CHARACTERISTICS

Surface-mounted, round LED light fitting, ingress protection class IP54, and an integrated energy-saving light source LED. White base; diffuser made of impact-resistant PC provides even light distribution and ensures a high impact resistance class (IK10).

APPLICATION

Surface mounted fitting intended for indoor use in representative rooms and passageways (large conference halls, hotel corridors, studies). Designed for mounting on ceilings and walls. Wide range of diameters and two diffuser versions allow for the same fitting to be used in rooms with different parameters. Well suited to be used as a basic or general interior light source.

The luminaire is intended for indoor traffic zones included in table 5.1 of the EN12464 standard.

GAMMA LED BASIC

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

GAMMA LED BASIC 220

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Dimensions (H/W/T/S) [mm]	Index
8	4000	800	OPAL		ø220/72	>> 226847
8	4000	800	OPAL	yes	ø220/72	>> 226854
8	4000	800	OPAL	yes	ø220/72	>> 226854/H


GAMMA LED BASIC 280

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Dimensions (H/W/T/S) [mm]	Index
10	3000	1100	OPAL		ø280/72	>> 226731/E
10	4000	1200	OPAL		ø280/72	>> 226779/E
10	3000	1100	OPAL	yes	ø280/72	>> 226724/E
10	3000	1100	OPAL	yes	ø280/72	>> 226724/EH
10	4000	1200	OPAL	yes	ø280/72	>> 226878/E
10	4000	1200	OPAL	yes	ø280/72	>> 226878/EH
13	4000	1500	OPAL		ø280/72	>> 226687
13	4000	1500	OPAL	yes	ø280/72	>> 226694
13	4000	1500	OPAL	yes	ø280/72	>> 226694/H

GAMMA LED BASIC

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



GAMMA LED

GAMMA LED BASIC

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
754968	Gamma LED Basic 280 1500lm 840 (13W) - light module



Gamma LED Basic 280 1500lm 840 (13W) - light module (754968)

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 102/2021; 391/2023; 49/2020



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl