

# MADERA 3 LED

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP44
<b>Nominal power [W]:</b>	15.00 - 41.00
<b>Luminous flux [lm]*:</b>	1800 - 5200
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	D; E
<b>Material of the body:</b>	powder coated steel
<b>Diffuser material:</b>	PS
<b>Diffuser type:</b>	OPAL; PRM
<b>Mounting version:</b>	surface
<b>Dimensions (H/W/T/S) [mm]:</b>	1170/350/68; 310/310/68; 480/480/68; 620/620/68; 620/350/68

## CHARACTERISTICS

Surface mounted, square LED fitting with high luminous flux, made of steel sheet, powder-coated grey; equipped with energy-saving light source LED. OPAL or PRM PMMA diffuser ensures even light distribution and no glare effect. Decorative fitting available in two diffuser sizes; optional equipment: radio motion sensor (RCR).

## APPLICATION

Surface-mounted luminaire intended for indoor use in offices or common rooms. Suitable as a general light source in representative rooms. Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. Product designed for surface mounting either on ceilings or on walls.

# MADERA 3 LED

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### MADERA 3 LED 1170/350/68mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Colour of the body	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
41	4000	5100	OPAL		white	1170/350/68	D	<a href="#">&gt;&gt; 497759</a>
41	4000	5100	OPAL		grey	1170/350/68	D	<a href="#">&gt;&gt; 497377</a>
41	4000	5200	PRM		white	1170/350/68	D	<a href="#">&gt;&gt; 497568</a>
41	4000	5200	PRM		grey	1170/350/68	D	<a href="#">&gt;&gt; 497186</a>

### MADERA 3 LED 310/310/68mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Colour of the body	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
15	3000	1800	OPAL		white	310/310/68	E	<a href="#">&gt;&gt; 497575</a>
15	3000	1800	OPAL		grey	310/310/68	E	<a href="#">&gt;&gt; 497193</a>
15	3000	1800	OPAL	yes	white	310/310/68	E	<a href="#">&gt;&gt; 497599</a>
15	3000	1800	OPAL	yes	grey	310/310/68	E	<a href="#">&gt;&gt; 497216</a>
15	4000	1850	OPAL		grey	310/310/68	E	<a href="#">&gt;&gt; 497209</a>
15	4000	1850	OPAL	yes	white	310/310/68	E	<a href="#">&gt;&gt; 497605</a>
15	4000	1850	OPAL	yes	grey	310/310/68	E	<a href="#">&gt;&gt; 497223</a>
15	4000	1850	OPAL		white	310/310/68	E	<a href="#">&gt;&gt; 497582</a>
15	3000	1800	PRM		white	310/310/68	E	<a href="#">&gt;&gt; 497384</a>
15	3000	1800	PRM		grey	310/310/68	E	<a href="#">&gt;&gt; 497001</a>
15	3000	1800	PRM	yes	white	310/310/68	E	<a href="#">&gt;&gt; 497407</a>
15	4000	1900	PRM		white	310/310/68	D	<a href="#">&gt;&gt; 497391</a>
15	4000	1900	PRM		grey	310/310/68	D	<a href="#">&gt;&gt; 497018</a>
15	4000	1900	PRM	yes	grey	310/310/68	D	<a href="#">&gt;&gt; 497032</a>
15	3000	1800	PRM	yes	grey	310/310/68	E	<a href="#">&gt;&gt; 497025</a>
15	4000	1900	PRM	yes	white	310/310/68	D	<a href="#">&gt;&gt; 497414</a>

### MADERA 3 LED 480/480/68mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Colour of the body	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
19	3000	2100	OPAL		white	480/480/68	E	<a href="#">&gt;&gt; 497612</a>
19	3000	2100	OPAL		grey	480/480/68	E	<a href="#">&gt;&gt; 497278</a>
19	3000	2100	OPAL	yes	white	480/480/68	E	<a href="#">&gt;&gt; 497636</a>
19	3000	2100	OPAL	yes	grey	480/480/68	E	<a href="#">&gt;&gt; 497292</a>
19	4000	2200	OPAL		white	480/480/68	E	<a href="#">&gt;&gt; 497626</a>
19	4000	2200	OPAL		grey	480/480/68	E	<a href="#">&gt;&gt; 497285</a>
19	4000	2200	OPAL	yes	white	480/480/68	E	<a href="#">&gt;&gt; 497643</a>

# MADERA 3 LED

## GENERAL CARD

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Colour of the body	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
19	4000	2200	OPAL	yes	grey	480/480/68	E	<a href="#">&gt;&gt; 497308</a>
19	3000	2150	PRM		white	480/480/68	E	<a href="#">&gt;&gt; 497650</a>
19	3000	2150	PRM		grey	480/480/68	E	<a href="#">&gt;&gt; 497087</a>
19	3000	2150	PRM	yes	white	480/480/68	E	<a href="#">&gt;&gt; 497674</a>
19	3000	2150	PRM	yes	grey	480/480/68	E	<a href="#">&gt;&gt; 497100</a>
19	4000	2250	PRM		white	480/480/68	E	<a href="#">&gt;&gt; 497667</a>
19	4000	2250	PRM		grey	480/480/68	E	<a href="#">&gt;&gt; 497094</a>
19	4000	2250	PRM	yes	white	480/480/68	E	<a href="#">&gt;&gt; 497681</a>
19	4000	2250	PRM	yes	grey	480/480/68	E	<a href="#">&gt;&gt; 497117</a>
26	3000	3100	OPAL		grey	480/480/68	E	<a href="#">&gt;&gt; 497230</a>
26	3000	3100	OPAL		white	480/480/68	E	<a href="#">&gt;&gt; 497469</a>
26	3000	3100	OPAL	yes	grey	480/480/68	E	<a href="#">&gt;&gt; 497254</a>
26	3000	3100	OPAL	yes	white	480/480/68	E	<a href="#">&gt;&gt; 497483</a>
26	4000	3250	OPAL		white	480/480/68	D	<a href="#">&gt;&gt; 497476</a>
26	4000	3250	OPAL		grey	480/480/68	D	<a href="#">&gt;&gt; 497247</a>
26	4000	3250	OPAL	yes	grey	480/480/68	D	<a href="#">&gt;&gt; 497261</a>
26	4000	3250	OPAL	yes	white	480/480/68	D	<a href="#">&gt;&gt; 497490</a>
26	3000	3150	PRM		white	480/480/68	E	<a href="#">&gt;&gt; 497421</a>
26	3000	3150	PRM		grey	480/480/68	E	<a href="#">&gt;&gt; 497049</a>
26	3000	3150	PRM	yes	white	480/480/68	E	<a href="#">&gt;&gt; 497445</a>
26	3000	3150	PRM	yes	grey	480/480/68	E	<a href="#">&gt;&gt; 497063</a>
26	4000	3300	PRM		white	480/480/68	D	<a href="#">&gt;&gt; 497438</a>
26	4000	3300	PRM		grey	480/480/68	D	<a href="#">&gt;&gt; 497056</a>
26	4000	3300	PRM	yes	white	480/480/68	D	<a href="#">&gt;&gt; 497452</a>
26	4000	3300	PRM	yes	grey	480/480/68	D	<a href="#">&gt;&gt; 497070</a>

## MADERA 3 LED 620/350/68mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Colour of the body	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
21	3000	2450	OPAL		white	620/350/68	E	<a href="#">&gt;&gt; 497735</a>
21	3000	2450	OPAL		grey	620/350/68	E	<a href="#">&gt;&gt; 497353</a>
21	4000	2550	OPAL		white	620/350/68	E	<a href="#">&gt;&gt; 497742</a>
21	4000	2550	OPAL		grey	620/350/68	E	<a href="#">&gt;&gt; 497360</a>
21	3000	2500	PRM		white	620/350/68	E	<a href="#">&gt;&gt; 497544</a>
21	3000	2500	PRM		grey	620/350/68	E	<a href="#">&gt;&gt; 497162</a>
21	4000	2600	PRM		white	620/350/68	E	<a href="#">&gt;&gt; 497551</a>
21	4000	2600	PRM		grey	620/350/68	E	<a href="#">&gt;&gt; 497179</a>

# MADERA 3 LED

## GENERAL CARD

### MADERA 3 LED 620/620/68mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Colour of the body	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
34	3000	4050	OPAL		white	620/620/68	E	<a href="#">&gt;&gt; 497698</a>
34	3000	4050	OPAL		grey	620/620/68	E	<a href="#">&gt;&gt; 497315</a>
34	4000	4250	OPAL		white	620/620/68	D	<a href="#">&gt;&gt; 497704</a>
34	4000	4250	OPAL		grey	620/620/68	D	<a href="#">&gt;&gt; 497322</a>
34	3000	4150	PRM		white	620/620/68	D	<a href="#">&gt;&gt; 497506</a>
34	3000	4150	PRM		grey	620/620/68	D	<a href="#">&gt;&gt; 497124</a>
34	4000	4350	PRM		white	620/620/68	D	<a href="#">&gt;&gt; 497513</a>
34	4000	4350	PRM		grey	620/620/68	D	<a href="#">&gt;&gt; 497131</a>
41	3000	4850	OPAL		white	620/620/68	E	<a href="#">&gt;&gt; 497711</a>
41	3000	4850	OPAL		grey	620/620/68	E	<a href="#">&gt;&gt; 497339</a>
41	4000	5100	OPAL		white	620/620/68	D	<a href="#">&gt;&gt; 497728</a>
41	4000	5100	OPAL		grey	620/620/68	D	<a href="#">&gt;&gt; 497346</a>
41	3000	4950	PRM		white	620/620/68	E	<a href="#">&gt;&gt; 497520</a>
41	3000	4950	PRM		grey	620/620/68	E	<a href="#">&gt;&gt; 497148</a>
41	4000	5200	PRM		white	620/620/68	D	<a href="#">&gt;&gt; 497537</a>
41	4000	5200	PRM		grey	620/620/68	D	<a href="#">&gt;&gt; 497155</a>

Card creation date: 27 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 145/2019; 254/2023