

COMPACT SOLID LED

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|----------------------------|---------------------------------|
| Ingress protection: | IP20 |
| Impact resistance: | IK07 |
| Nominal power [W]: | 24.00 - 60.00 |
| Luminous flux [lm]*: | 2950 - 8100 |
| Colour rendering index: | 80 |
| SDCM: | ≤ 3 |
| UGR (4H8H): | < 19 |
| Energy efficiency class: | A+; A++ |
| Material of the body: | ABS + powder coated steel sheet |
| Diffuser material: | PC |
| Diffuser type: | OPAL; PRM |
| Mounting version: | surface |
| Dimensions (H/W/T/S) [mm]: | 71/620/620; |
| Warranty [years]: | 5 |

CHARACTERISTICS

Compact LED luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED panels and an evenly highlighted opal or prismatic difuser, providing low glare (UGR<19)* . Made of powder caoated steel sheet and plastic. Assembly or electrical connection does not require removing the diffuser.

* The UGR coefficient is met for the typical use of the luminaire

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 modular ceilings.

COMPACT SOLID LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

COMPACT SOLID LED 24W

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Electrical protection class | Index |
|-------------------|------------------------|---------------------|---------------|-----------------------------|---------------------------------|
| 24 | 4000 | 2950 | OPAL | II | >> 009631 |
| 24 | 3000 | 3300 | PRM | II | >> 009648 |
| 24 | 4000 | 3550 | PRM | II | >> 009655 |

COMPACT SOLID LED 32W

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Electrical protection class | Index |
|-------------------|------------------------|---------------------|---------------|-----------------------------|---------------------------------|
| 32 | 4000 | 3800 | OPAL | II | >> 009662 |
| 32 | 3000 | 4250 | PRM | II | >> 009679 |
| 32 | 4000 | 4550 | PRM | II | >> 009686 |

COMPACT SOLID LED 42W

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Electrical protection class | Index |
|-------------------|------------------------|---------------------|---------------|-----------------------------|---------------------------------|
| 42 | 4000 | 4800 | OPAL | II | >> 009693 |
| 42 | 3000 | 5350 | PRM | II | >> 009709 |
| 42 | 4000 | 5750 | PRM | II | >> 009716 |

COMPACT SOLID LED 52W

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Electrical protection class | Index |
|-------------------|------------------------|---------------------|---------------|-----------------------------|---------------------------------|
| 52 | 4000 | 5450 | OPAL | II | >> 009723 |
| 52 | 4000 | 6550 | PRM | II | >> 009730 |


COMPACT SOLID LED 60W

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Electrical protection class | Index |
|-------------------|------------------------|---------------------|---------------|-----------------------------|---------------------------------|
| 60 | 4000 | 6750 | OPAL | I | >> 009747 |
| 60 | 4000 | 8100 | PRM | I | >> 009754 |


COMPACT SOLID LED

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



COMPACT SOLID LED OPAL




COMPACT SOLID LED PRM

COMPACT SOLID LED

GENERAL CARD

ACCESSORIES AVAILABLE

| index | Name |
|-------|-----------------------------|
| | COMPACT SOLID – steel frame |



COMPACT SOLID – steel frame (009624)