NECTRA LITE LED

GENERAL CARD

TECHNICAL PARAMETERS

Ingress protection:	IP20; IP44/20
Nominal power [W]:	14.00 - 25.00
Luminous flux [lm]*:	1330 - 2450
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Electrical protection class:	II
Energy efficiency class:	E
Material of the body:	PC; PC + steel
Colour of the body:	white
Diffuser type:	OPAL
Dimensions (H/W/T/S) [mm]:	145/66; 174/69; 224/84; 88/228/228;
Mounting version:	recessed; surface
Warranty [years]:	5

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

NECTRA LITE LED

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

NECTRA LITE LED surface

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Ingress protection	Energy efficiency class	Mounting version	Index
20	4000	2000	OPAL	88/228/228	IP20	E	surface	>> 502644
25	4000	2450	OPAL	88/228/228	IP20	E	surface	>> 502651


NECTRA LITE LED recessed

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Ingress protection	Energy efficiency class	Mounting version	Index
14	4000	1330	OPAL	145/66	IP44/20	E	recessed	>> 502606
17	4000	1650	OPAL	174/69	IP44/20	E	recessed	>> 502613
20	4000	2000	OPAL	224/84	IP44/20	E	recessed	>> 502620
25	4000	2450	OPAL	224/84	IP44/20	E	recessed	>> 502637


NECTRA LITE LED

GENERAL CARD


LUMINOUS INTENSITY DISTRIB. CURVE




NECTRA LITE LED 14W



NECTRA LITE LED 17W



NECTRA LITE LED 20W



NECTRA LITE LED 25W

Card creation date: 29 April 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 344/2023; 346/2023; 79/2020; 82/2020

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl