

VECTOR 3 MULTI LED

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|-----------------------------------|--|
| Ingress protection: | IP40 |
| Impact resistance: | IK07 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | A+ |
| Material of the body: | powder coated steel |
| Diffuser material: | PC |
| Diffuser type: | PRM MAT |
| Mounting version: | surface |
| Dimensions (H/W/T/S) [mm]: | 601/61/125; 1161/61/125; 1441/126/60; |
| Warranty [years]: | 5 |

CHARACTERISTICS

Surface mounted luminaire made of powder coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED GO! modules with high luminous efficacy and SDCM <3. The luminaire in standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

The MULTI luminaire version allows individual configuration: thanks to the built-in microswitch, it is possible to choose one of four settings (nominal power of the fitting [W] / luminous flux of the fitting [lm]):

- 13W-24W - 13/1700; 17/2100; 20/2450; 24/2750;
- 26W-48W - 26/3350; 34/4150; 40/4900; 48/5700;
- 34W-59W - 34/4200; 42/5150; 51/6000; 59/6900.

APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings). The luminaire is intended for general areas inside buildings – store rooms and storage rack areas as well as cold stores included in tables 5.4 and 5.5 of the EN12464 standard; for indoor traffic zones included in table 5.1 of the EN12464 standard and for parking areas and as lighting of railway installations included in table 5.34 and 5.53 of the EN12464 standard, excluding ticket and luggage offices, counters, waiting rooms, entrance halls and lounges.

VECTOR 3 MULTI LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

VECTOR 3 MULTI LED 13/17/20/24W

| Nominal power [W] - range | Colour temperature [K] | Luminous flux of the luminaire [lm] - range | Diffuser type | Motion sensor | Through wiring | Emergency lighting [h] | Dimensions (H/W/T/S) [mm] | Energy efficiency class | Index |
|---------------------------|------------------------|---|---------------|---------------|----------------|------------------------|---------------------------|-------------------------|---------------------------------|
| 13/17/20/24 | 4000 | 1700/2100/2450/2750 | PRM MAT | | | | 601/61/125 | A+ | >> 661891 |
| 13/17/20/24 | 4000 | 1700/2100/2450/2750 | PRM MAT | yes | | | 601/61/125 | A+ | >> 661945 |

VECTOR 3 MULTI LED 26/34/40/48W

| Nominal power [W] - range | Colour temperature [K] | Luminous flux of the luminaire [lm] - range | Diffuser type | Motion sensor | Through wiring | Emergency lighting [h] | Dimensions (H/W/T/S) [mm] | Energy efficiency class | Index |
|---------------------------|------------------------|---|---------------|---------------|----------------|------------------------|---------------------------|-------------------------|---------------------------------|
| 26/34/40/48 | 4000 | 3350/4150/4900/5700 | PRM MAT | | | | 1161/61/125 | A+ | >> 661907 |
| 26/34/40/48 | 4000 | 3350/4150/4900/5700 | PRM MAT | | | 3 | 1161/61/125 | A+ | >> 661976 |
| 26/34/40/48 | 4000 | 3350/4150/4900/5700 | PRM MAT | yes | | | 1161/61/125 | A+ | >> 661952 |
| 26/34/40/48 | 4000 | 3350/4150/4900/5700 | PRM MAT | | LS2 | | 1161/61/125 | A+ | >> 661921 |


VECTOR 3 MULTI LED 34/42/51/59W

| Nominal power [W] - range | Colour temperature [K] | Luminous flux of the luminaire [lm] - range | Diffuser type | Motion sensor | Through wiring | Emergency lighting [h] | Dimensions (H/W/T/S) [mm] | Energy efficiency class | Index |
|---------------------------|------------------------|---|---------------|---------------|----------------|------------------------|---------------------------|-------------------------|---------------------------------|
| 34/42/51/59 | 4000 | 4200/5150/6000/6900 | PRM MAT | | | | 1441/126/60 | A+ | >> 661914 |
| 34/42/51/59 | 4000 | 4200/5150/6000/6900 | PRM MAT | | | 3 | 1441/126/60 | A+ | >> 661983 |
| 34/42/51/59 | 4000 | 4200/5150/6000/6900 | PRM MAT | yes | | | 1441/126/60 | A+ | >> 661969 |
| 34/42/51/59 | 4000 | 4200/5150/6000/6900 | PRM MAT | | LS2 | | 1441/126/60 | A+ | >> 661938 |

VECTOR 3 MULTI LED

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



VECTOR 3 MULTI LED

Card creation date: 24 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 331/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl