

# CAPELLA LED VD

GENERAL CARD



## TECHNICAL PARAMETERS

Nominal power [W]:	16.00 - 24.00
Luminous flux [lm]*:	1400 - 2500

## CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

## APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

# CAPELLA LED VD

---

GENERAL CARD

## AVAILABLE VERSIONS

---




Click index >>, to see details


# CAPELLA LED VD

## GENERAL CARD

## LUMINOUS INTENSITY DISTRIB. CURVE



CAPELLA LED



CAPELLA LED EDGE

Card creation date:10 September 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 156/2020



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl