

EXPO SYSTEM LED FOR

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Nominal power [W]:	18.00 - 28.00
Luminous flux [lm]*:	1100 - 3100
Energy efficiency class:	E; F; G
Material of the body:	aluminium
Diffuser material:	PMMA
Diffuser type:	lens
Mounting version:	track, surface
Dimensions (H/W/T/S) [mm]:	Ø85/255; art; bakery; fashion; fish and seafood; fresh meat; fruit nad vegetables; meat
Version:	

CHARACTERISTICS

High quality aluminum projector with LED COB light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability. Immediate ignition without flicker makes it the best replacement for metal halide or halogen sources projectors.

Available versions dedicated to lighting:

meat, fresh meat, fruits and vegetables, fish and seafood, bread (gold), works of art (art), clothing (fashion).

Accessories:

- base for surface mounting,
- honeycomb that reduces glare.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector

EXPO SYSTEM LED FOR

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

EXPO SYSTEM LED FOR art

Nominal power [W]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	Energy efficiency class	Index
18	1550	15	white	F	>> 253645
18	1550	15	black	F	>> 253287
18	1550	24	white	F	>> 253706
18	1550	24	black	F	>> 253348
18	1600	36	white	F	>> 253768
18	1600	36	black	F	>> 253409
28	2550	15	white	F	>> 253461
28	2550	15	black	F	>> 253102
28	2550	24	white	F	>> 253522
28	2550	24	black	F	>> 253164
28	2550	36	white	F	>> 253584
28	2550	36	black	F	>> 253225

EXPO SYSTEM LED FOR fresh meat

Nominal power [W]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	Energy efficiency class	Index
18	1100	15	white	G	>> 253614
18	1100	15	black	G	>> 253256
18	1100	24	white	G	>> 253676
18	1100	24	black	G	>> 253317
18	1150	36	white	G	>> 253737
18	1150	36	black	G	>> 253379
28	1900	15	white	G	>> 253430
28	1900	15	black	G	>> 253072
28	1900	24	white	G	>> 253492
28	1900	24	black	G	>> 253133
28	1900	36	white	G	>> 253553
28	1900	36	black	G	>> 253195

EXPO SYSTEM LED FOR fashion

Nominal power [W]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	Energy efficiency class	Index
18	1700	15	white	F	>> 253652
18	1700	15	black	F	>> 253294
18	1700	24	white	F	>> 253713
18	1700	24	black	F	>> 253355
18	1750	36	white	F	>> 253775

EXPO SYSTEM LED FOR

GENERAL CARD

Nominal power [W]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	Energy efficiency class	Index
18	1750	36	black	F	>> 253416
28	2850	15	white	E	>> 253478
28	2850	15	black	E	>> 253119
28	2850	24	white	E	>> 253539
28	2850	24	black	E	>> 253171
28	2850	36	white	E	>> 253591
28	2850	36	black	E	>> 253232

EXPO SYSTEM LED FOR fruit nad vegetables

Nominal power [W]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	Energy efficiency class	Index
18	1600	15	white	F	>> 253621
18	1600	15	black	F	>> 253263
18	1600	24	white	F	>> 253683
18	1600	24	black	F	>> 253324
18	1650	36	white	F	>> 253744
18	1650	36	black	F	>> 253386
28	2650	15	white	F	>> 253447
28	2650	15	black	F	>> 253089
28	2650	24	white	F	>> 253508
28	2650	24	black	F	>> 253140
28	2650	36	white	F	>> 253560
28	2650	36	black	F	>> 253201

EXPO SYSTEM LED FOR bakery

Nominal power [W]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	Energy efficiency class	Index
18	1700	15	white	F	>> 253874
18	1700	15	black	F	>> 253812
18	1700	24	white	F	>> 253881
18	1700	24	black	F	>> 253829
18	1750	36	white	F	>> 253898
18	1750	36	black	F	>> 255137
28	2850	15	white	E	>> 253843
28	2850	15	black	E	>> 253782
28	2850	24	white	E	>> 253850
28	2850	24	black	E	>> 253799
28	2850	36	white	E	>> 253867
28	2850	36	black	E	>> 253805

EXPO SYSTEM LED FOR

GENERAL CARD

EXPO SYSTEM LED FOR fish and seafood

Nominal power [W]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	Energy efficiency class	Index
18	1850	15	white	F	>> 253638
18	1850	15	black	F	>> 253270
18	1850	24	white	F	>> 253690
18	1850	24	black	F	>> 253331
18	1900	36	white	E	>> 253751
18	1900	36	black	E	>> 253393
28	3100	15	white	E	>> 253454
28	3100	15	black	E	>> 253096
28	3100	24	white	E	>> 253515
28	3100	24	black	E	>> 253157
28	3100	36	white	E	>> 253577
28	3100	36	black	E	>> 253218

EXPO SYSTEM LED FOR meat

Nominal power [W]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	Energy efficiency class	Index
18	1100	15	white	G	>> 253607
18	1100	15	black	G	>> 253249
18	1100	24	white	G	>> 253669
18	1100	24	black	G	>> 253300
18	1150	36	white	G	>> 253720
18	1150	36	black	G	>> 253362
28	1900	15	white	G	>> 253423
28	1900	15	black	G	>> 253065
28	1900	24	white	G	>> 253485
28	1900	24	black	G	>> 253126
28	1900	36	white	G	>> 253546
28	1900	36	black	G	>> 253188

EXPO SYSTEM LED FOR

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
255106	EXPO SYSTEM LED surface mounting base black
255120	EXPO SYSTEM LED honeycomb



EXPO SYSTEM LED surface mounting base black (255106)



EXPO SYSTEM LED honeycomb (255120)

Card creation date: 20 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 45/2020