

DIONE LED PLUS MULTI

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W] - range:	10/12/15/17; 10/12/16/19; 15/18/22/26; 15/19/22/26
Luminous flux of the luminaire [lm] - range:	1650/1900/2300/2610; 1650/2000/2320/2650; 1650/2030/2320/2650; 1800/2100/2400/2800
Colour temperature [K]:	3000; 4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS; Biały
Diffuser material:	PC
Diffuser type:	OPAL
Dimensions (H/W/T/S) [mm]:	340x115; 340/115; 140; ø340/115;
Warranty [years]:	5

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

The MULTI luminaire version allows individual configuration: thanks to the built-in micoswitch, it is possible to choose one of 4 settings (nominal power of the fitting [W] / luminous flux of the fitting [lm]).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS MULTI

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

DIONE LED PLUS MULTI 15/18/22/26W


Nominal power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Diffuser type	Motion sensor	Corridor function	Emergency lighting [h]	Autotest	Index
15/18/22/26	3000	1650/1900/2300/2610	OPAL			3	yes	>> 951855
15/18/22/26	3000	1650/1900/2300/2610	OPAL					>> 951800
15/18/22/26	3000	1650/1900/2300/2610	OPAL	yes		3	yes	>> 951879
15/18/22/26	3000	1650/1900/2300/2610	OPAL	yes				>> 951831
15/18/22/26	4000	1650/2000/2320/2650	OPAL			3	yes	>> 951862
15/18/22/26	4000	1650/2000/2320/2650	OPAL					>> 951794
15/18/22/26	4000	1650/2000/2320/2650	OPAL	yes		3	yes	>> 951886
15/18/22/26	4000	1650/2000/2320/2650	OPAL	yes				>> 951848
15/18/22/26	4000	1650/2000/2320/2650	OPAL	yes				>> 940743
15/18/22/26	3000	1650/1900/2300/2610	OPAL	yes				>> 943287
15/18/22/26	3000	1800/2100/2400/2800	OPAL		yes			>> 943836
15/18/22/26	4000	1800/2100/2400/2800	OPAL		yes			>> 943843

DIONE LED PLUS MULTI

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant




Ceiling ring Dione LED steel 1.5 white
matt RAL 9003 painted vandal
resistant (120DL118)

Card creation date:10 June 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 379/2023; 80/2020



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl

