

OCULUS LED UGR 18700LM 840 IP66 I CL. SP10KV 129W

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	129
Luminous flux [lm]*:	18700
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Electrical protection class:	I
Material of the body:	powder coated aluminium
Colour of the body:	grey

CHARACTERISTICS

A HIGH-BAY luminaire from the NEXT GEN product line, constituting a new generation of luminaires dedicated to LED technology. The designed-from-scratch body – made of die-cast aluminium and powder-coated – uses natural conduction and convection processes, which have a positive effect on the luminaire's heat management. The shape of the body with an integrated, effective heat sink and high-quality materials ensure maximum heat dissipation from the LED module. The driver's external compartment, separated from the body, guarantees optimal thermal working conditions for the power supply system. This enables the luminaire to work at an ambient temperature of max 60°C. LEDs from a reputable manufacturer and new LED modules enable very high luminous efficiency. This guarantees that the required lighting level and significant energy savings are achieved. The diffuser and optical system are composed of precise lenses made of polycarbonate (PC). Standard equipped with a 0.3 m long H07RN-F cable terminated with an additional male and female connector, which makes the assembly easier and more convenient. Its design is adapted for suspended mounting and surface mounting (ceiling and wall) requiring the use of additional accessories. A UGR (Unified Glare Rating) of less than 19 minimizes the effect of glare affecting well-being, reducing fatigue and fewer mistakes.

APPLICATION

The luminaire is designed for suspended mounting using chains, ropes, etc. and with the use of additional accessories also surface-mounted (ceiling and wall) indoors. It works perfectly in factories and production halls as well as large-scale warehouses and logistics centers.

OCULUS LED UGR 18700LM 840 IP66 I CL. SP10KV 129W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	561214	Diffuser type:	transparent
Rated power of the luminaire [W]:	129	Optics material:	PC
Luminous flux [lm]:	18700	Optics:	lens
Supply voltage [V]:	220 - 240	Material of the body:	powder coated aluminium
Frequency [Hz]:	50 - 60	Colour of the body:	grey
Luminous efficacy [lm/W]:	145	Dimensions (H/W/T/S) [mm]:	106/371
Electrical protection class:	I	Impact resistance:	IK09
Colour temperature [K]:	4000	Ingress protection:	IP66
Colour rendering index:	>80	Working temperature [°C]:	from -25 to +60
SDCM:	≤ 3	Cable length [m]:	0.30
Power factor:	0.99	Net weight of the luminaire [kg]:	3.420
LED lifespan L70B50 [h]:	196000	Warranty [years]:	5
LED lifespan L80B20 [h]:	123000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L90B10 [h]:	60000	Warranty [years]:	5
Beam angle [°]:	55	CE certificate:	154/2023
Surge protection [kV]:	10	PZH certificate:	B-BK-60212-0481/21
Diffuser material:	PC	Manual:	Download PDF

OCULUS LED UGR 18700LM 840 IP66 I CL. SP10KV 129W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
964244	OCULUS LED - RCR motion sensor
963674	OCULUS LED - RCR / PIR DALI motion sensor



OCULUS LED - RCR motion sensor (964244)



OCULUS LED - RCR / PIR DALI motion sensor (963674)

Card creation date: 09 February 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 154/2023