

# MAGNUM 36W 24V WITHOUT SOCKET WITH CEE PLUG

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP44
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	36
<b>Supply voltage [V]:</b>	24
<b>Electrical protection class:</b>	III
<b>Material of the body:</b>	PP
<b>Colour of the body:</b>	black
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	transparent
<b>Dimensions (H/W/T/S) [mm]:</b>	340/230/110

## CHARACTERISTICS

- Power: 36W
- Light source: TC-L fluorescent tubes (2x18W)
- Lamp-holder: 2G11
- Ballast type: EVG
- Ingress protection class: IP54
- Polycarbonate prismatic diffuser
- Impact-resistant casing and multi-positional arm
- Rubber cable H07RN-F 2x1,0mm<sup>2</sup> (5m)
- Weight: 2 -2,4 kg

Optionally available:

- One socket at the back side of the fitting
- Rubber cable H07RN-F 3x1,5mm<sup>2</sup> (5m)
- VVG (KVG) ballast

## APPLICATION

# MAGNUM 36W 24V WITHOUT SOCKET WITH CEE PLUG

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	888076	<b>Impact resistance:</b>	IK10
<b>EAN:</b>	5905963888076	<b>Ingress protection:</b>	IP44
<b>Light source:</b>	LED	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Nominal power [W]:</b>	36	<b>Plug type:</b>	CEE
<b>Supply voltage [V]:</b>	24	<b>Wire type:</b>	H07RN-F
<b>Electrical protection class:</b>	III	<b>Cable length [m]:</b>	5
<b>Beam angle [°]:</b>	120	<b>Net weight of the luminaire [kg]:</b>	2
<b>Light colour:</b>	biały	<b>Warranty [years]:</b>	2
<b>Exchangeable source:</b>	yes	<b>Category type:</b>	workplace floodlights
<b>Diffuser material:</b>	PC	<b>ETIM class:</b>	EC000346
<b>Diffuser type:</b>	transparent	<b>Warranty [years]:</b>	2
<b>Material of the body:</b>	PP	<b>CE certificate:</b>	<a href="#">07/2009</a>
<b>Colour of the body:</b>	black	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Dimensions (H/W/T/S) [mm]:</b>	340/230/110		

Card creation date: 17 December 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 07/2009