

MAGNUM 36W 24V WITHOUT SOCKET WITH TRANSFORMER PLUG

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	36
Supply voltage [V]:	24
Electrical protection class:	III
Material of the body:	PP
Colour of the body:	black
Diffuser material:	PC
Diffuser type:	transparent
Dimensions (H/W/T/S) [mm]:	340/230/110

CHARACTERISTICS

- Power: 36W
- Light source: TC-L fluorescent tubes (2x18W)
- Lamp-holder: 2G11
- Ballast type: EVG
- Ingress protection class: IP54
- Polycarbonate prismatic diffuser
- Impact-resistant casing and multi-positional arm
- Rubber cable H07RN-F 2x1,0mm² (5m)
- Weight: 2 -2,4 kg

Optionally available:

- One socket at the back side of the fitting
- Rubber cable H07RN-F 3x1,5mm² (5m)
- VVG (KVG) ballast

APPLICATION

MAGNUM 36W 24V WITHOUT SOCKET WITH TRANSFORMER PLUG

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	888403	Impact resistance:	IK10
EAN:	5905963888403	Ingress protection:	IP44
Light source:	LED	Working temperature [°C]:	from -20 to +35
Nominal power [W]:	36	Plug type:	TRAFO
Supply voltage [V]:	24	Wire type:	H07RN-F
Electrical protection class:	III	Cable length [m]:	5
Beam angle [°]:	120	Net weight of the luminaire [kg]:	2
Light colour:	biały	Warranty [years]:	2
Exchangeable source:	yes	Category type:	workplace floodlights
Diffuser material:	PC	ETIM class:	EC000346
Diffuser type:	transparent	Warranty [years]:	2
Material of the body:	PP	CE certificate:	07/2009
Colour of the body:	black	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	340/230/110		

Card creation date: 17 December 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 07/2009