

PROFI LED 4W PC TRANSPARENT WITH UNIVERSAL PLUG

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	4
Luminous flux [lm]*:	450
Colour temperature [K]:	4000
Ingress protection:	IP54
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	II
Colour rendering index:	>80
Material of the body:	gum
Dimensions (H/W/T/S) [mm]:	60/415

CHARACTERISTICS

- Power: 4W, 5W
- Luminous flux: 450lm, 700lm
- 65% less power consumption (compared to Profi 11W)
- Light source: SMD LED
- Polycarbonate impact-resistant prismatic diffuser
- Handle and cap made of rubber
- High ingress protection class IP54
- Rotating hook
- Weight: 0,7 kg
- Rubber cable H05RN-F 2x1 mm² (5m)
- Spare parts available

APPLICATION

PROFI LED 4W PC TRANSPARENT WITH UNIVERSAL PLUG

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	260834	Colour of the body:	black
EAN:	5905963260834	Dimensions (H/W/T/S) [mm]:	60/415
Light source:	LED	Ingress protection:	IP54
Nominal power [W]:	4	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	450	Plug type:	UNI-SCHUKO
Supply voltage [V]:	220 - 240	Hook:	yes
Frequency [Hz]:	50 - 60	Net weight [kg]:	0.700
Electrical protection class:	II	Warranty [years]:	2
Colour temperature [K]:	4000	ETIM class:	EC000347
Colour rendering index:	>80	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PC	Warranty [years]:	2
Diffuser type:	transparent	CE certificate:	258/2023
Material of the body:	gum	Manual:	Download PDF

PROFI LED 4W PC TRANSPARENT WITH UNIVERSAL PLUG

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
111631	
886584	Magnetic rubber mount



Magnetic rubber mount (886584)

Card creation date: 17 December 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 258/2023