

EXPO ADJUST 3200LM DALI 36° BLACK 940 35W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	35
Luminous flux [lm]*:	3200
Colour temperature [K]:	4000
Diffuser material:	PC
Diffuser type:	clear
Diffuser colour:	transparent
Material of the body:	aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	260/185/95
Warranty [years]:	5

CHARACTERISTICS

EXPO ADJUST is the highest quality aluminum projector with a COB LED light source. The system of branded busbars on which the projectors are mounted increases the range of applications and allows the user to make changes to the arrangement after the installation. Compact, small size, aluminum body with a heat sink effectively dissipates excess heat from the projector and increases the product life. An Anesthetic ABS box effectively masks the power supply inside.

APPLICATION

No emission of ultraviolet and infrared radiation and a high color rendering index (Ra >90), combined with the highest luminous efficiency and excellent product durability, allows the use of EXPO ADJUST wherever the highest quality of light is expected while maintaining energy efficiency. The main areas of application are accent lighting in commercial facilities, museums, exhibition halls, offices, and apartments.

The ZOOM version with adjustable lighting angle in the range of 22-55° increases the adaptive value of the product in the event of a change in the decor or the need for a different display of goods compared to the original assumptions.

EXPO ADJUST 3200LM DALI 36° BLACK 940 35W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	481567	Optics material:	PC
EAN:	5905963481567	Optics:	lens
Light source:	COB	Material of the body:	aluminium
Nominal power [W]:	33.50	Colour of the body:	black
Rated power of the luminaire [W]:	35	Dimensions (H/W/T/S) [mm]:	260/185/95
Supply voltage [V]:	220 – 240	Ingress protection:	IP20
Frequency [Hz]:	50 - 60	Mounting version:	track
Luminous flux [lm]:	3200	Working temperature [°C]:	from -20 to +25
Luminous efficacy [lm/W]:	92	Beam angle adjustment [°]:	no; 36°
Electrical protection class:	II	Energy efficiency class:	G
Colour temperature [K]:	4000	DIMM DALI:	yes
Colour rendering index:	>90	Control:	DALI
SDCM:	≤ 3	Net weight of the luminaire [kg]:	0.660
Beam angle [°]:	36	Light distribution type:	symmetric
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	clear	CE certificate:	33/2022
Diffuser colour:	transparent	Manual:	Download PDF

Card creation date: 31 May 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 33/2022