TERRACO DIR LED 690LM PLX IP54 I CL. 840 17W GREY

DETAILED CARD



TECHNICAL PARAMETERS

Index:	995262
Light source:	LED module
Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	690
Energy efficiency class:	G
Electrical protection class:	I
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Exchangeable source:	yes
Material of the body:	Steel

CHARACTERISTICS

Terraco LED is a modernist luminaire distinguished by its interesting minimalist design. The powder-coated aluminium body of the lamp is available in four colour versions: grey, graphite, white and black. The multitude of versions with different luminous surfaces allows it to be used in a variety of places and in different ways: vertically and horizontally. Installed on a building façade, it can shine downwards, upwards and sideways. It has a high ingress protection rating of IP54. It is designed for surface mounting.

APPLICATION

The Terraco LED lamp will be particularly suitable as outdoor facade lighting, terrace lighting, and balcony lighting. Small dimensions increase the range of its applications - it can illuminate alcoves or hard-to-reach places. Terraco lamps can also be used in the interiors of buildings and arranged in a variety of ways on the wall to form interesting lighting arrangements. The lamp allows to realize a large number of interesting lighting concepts. It is used to illuminate contemporary architecture.


TERRACO DIR LED 690LM PLX IP54 I CL. 840 17W GREY

DETAILED CARD


TECHNICAL PARAMETERS TABLE

Index:	995262	**Light distribution type:**	DIR
EAN:	5905963995262	**Optics:**	general
Light source:	LED module	**Exchangeable source:**	yes
Rated power of the luminaire [W]:	17	**Diffuser material:**	PMMA
Luminous flux [lm]:	690	**Diffuser type:**	matt
AC voltage range [V]:	220 - 240	**Diffuser colour:**	white
Frequency [Hz]:	50-60	**Material of the body:**	Steel
Luminous efficacy [lm/W]:	42	**Colour of the body:**	gray RAL 9006
Energy efficiency class:	G	**Dimensions (H/W/T/S) [mm]:**	260/110/100
Electrical protection class:	I	**Impact resistance:**	IK04
Colour temperature [K]:	4000	**Ingress protection:**	IP54
Color rendering index (Ra) >:	80	**Mounting version:**	surface
SDCM:	4	**Working temperature [°C]:**	from -25 to +35
LED lifespan L70B50 [h]:	134000	**CE certificate:**	90/2025
LED lifespan L80B10 [h]:	86000	**Manual:**	Download PDF
LED lifespan L90B10 [h]:	46000	**Category of application:**	architectural

TECHNICAL DETAILS



Dir



Dir

Card creation date: 19 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 90/2025

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl