

OCULUS LED F 24200LM 840 IP65 I KL. 55D 156W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	156
Luminous flux [lm]*:	24200
Supply voltage [V]:	100 - 277
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	155
Energy efficiency class:	C
Electrical protection class:	I
Colour temperature [K]:	4000
Impact resistance:	IK09
Ingress protection:	IP65

CHARACTERISTICS

OCULUS LED is a HIGH-BAY luminaire from the NEXT GEN product line, constituting a new generation of luminaires dedicated to LED technology. The designed-from-scratch body – made of die-cast aluminium and powder coated – uses natural conduction and convection processes, which have a positive effect on luminaire's heat management. The shape of the body with an integrated, effective heat sink and high-quality materials ensure maximum heat dissipation from the LED module. The driver's external compartment, separated from the body, guarantees optimal thermal working conditions for the power supply system. This enables the luminaire to work in an ambient temperature of max 60°C. LEDs from a reputable manufacturer and new LED modules enable very high luminous efficiency: max 176 lm/W. This guarantees that the required lighting level and significant energy savings are achieved. The diffuser and optical system are composed of precise linear lenses made of polycarbonate (PC). There are 3 dedicated ranges of light distribution available: 55°, 75°, 105°. GLASS version with tempered glass (without lenses) and 105° distribution is also available.

Standard equipped with a 0.3 m long H07RN-F cable terminated with an additional male and female connector, which makes the assembly easier and more convenient.

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

Its design is adapted for suspended mounting and surface mounting (ceiling and wall) requiring the use of additional accessories.

APPLICATION

The luminaire is intended for suspended mounting (using chains, wires, etc.) both indoors and outdoors. It will prove perfect for manufacturing plants and halls as well as large-format warehouses and logistics centres.

OCULUS LED F 24200LM 840 IP65 I KL. 55D 156W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	977435	Surge protection [kV]:	6
EAN:	5905963977435	Diffuser material:	PC
Rated power of the luminaire [W]:	156	Diffuser type:	transparent
Luminous flux [lm]:	24200	Optics:	lens
Supply voltage [V]:	100 - 277	Optics material:	PC
Frequency [Hz]:	50-60	Material of the body:	powder coated aluminium
Luminous efficacy [lm/W]:	155	Colour of the body:	grey
Energy efficiency class:	C	Dimensions (H/W/T/S) [mm]:	106/371
Electrical protection class:	I	Impact resistance:	IK09
Colour temperature [K]:	4000	Ingress protection:	IP65
Colour rendering index:	80	Working temperature [°C]:	from -40 to +50
SDCM:	≤ 3	Cable length [m]:	0.30
Power factor:	0.95	Dimensions of single box [mm]:	135/372/372
ITHD [%]:	7	Number on the palette [pcs]:	66
Flicker procent:	5	Net weight [kg]:	3.400
LED lifespan L70B50 [h]:	196000	Warranty [years]:	5
LED lifespan L80B20 [h]:	123000	Manual:	Download PDF
LED lifespan L90B10 [h]:	60000	CE certificate:	143/2022
Beam angle [°]:	55		

OCULUS LED F 24200LM 840 IP65 I KL. 55D 156W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
964244	OCULUS LED - RCR motion sensor
964886	OCULUS LED - universal handle
964893	OCULUS LED - surface mounting handle
964862	OCULUS LED - protective grid
963674	OCULUS LED - RCR / PIR DALI motion sensor
WSEL438	WSEL438 HD01R Remote control for motion sensor
WSEL415	WSEL415 Remote control for - PIR sensor



OCULUS LED - RCR motion sensor (964244)



OCULUS LED - universal handle (964886)



OCULUS LED - surface mounting handle (964893)



OCULUS LED - protective grid (964862)



OCULUS LED - RCR / PIR DALI motion sensor (963674)



WSEL438 HD01R Remote control for motion sensor (WSEL438)



WSEL415 Remote control for - PIR sensor (WSEL415)

Card creation date: 17 August 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 143/2022



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl