

RQ 220 LED N 2100LM DALI 840 IP20 II CL. PRM 17W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	2100
Luminous efficacy [lm/W]:	124
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	4000
Colour rendering index:	>80
Beam angle [°]:	110
Diffuser type:	PRM
Material of the body:	ABS

CHARACTERISTICS

RQ 220 LED N is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

RQ 220 LED N 2100LM DALI 840 IP20 II CL. PRM 17W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	947254	Colour of the body:	white
EAN:	5905963947254	Dimensions (H/W/T/S) [mm]:	227/227/86
Light source:	LED module	Mounting dimensions [mm]:	rostaw otworów50x50, śruba ∅5,5mm
Rated power of the luminaire [W]:	17	Impact resistance:	IK07
Luminous flux [lm]:	2100	Ingress protection:	IP20
Luminous efficacy [lm/W]:	124	Mounting version:	surface
Energy efficiency class:	D	Working temperature [°C]:	from 0 to +35
Electrical protection class:	II	CE certificate:	298/2023
Colour temperature [K]:	4000	Manual:	Download PDF
Colour rendering index:	>80	DIMM DALI:	yes
Beam angle [°]:	110	Category type:	downlights
Diffuser material:	PC	LED lifespan L70B50 [h]:	92000
Diffuser type:	PRM	LED lifespan L80B20 [h]:	58000
Material of the body:	ABS	LED lifespan L90B10 [h]:	28000

RQ 220 LED N 2100LM DALI 840 IP20 II CL. PRM 17W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
947353	Suspension RQ220 f100 white ON/OFF. DALI

Card creation date: 10 August 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 298/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl