

RQ 220 LED P 2200LM 830 IP65/IP20 I CL. AW3H MAT 19W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	19
Luminous flux [lm]*:	2000
Luminous efficacy [lm/W]:	106
Energy efficiency class:	E
Electrical protection class:	I
Colour temperature [K]:	3000
Diffuser material:	PC
Diffuser type:	MAT
Material of the body:	ABS
Colour of the body:	white

CHARACTERISTICS

RQ 220 LED P is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

RQ 220 LED P 2200LM 830 IP65/IP20 I CL. AW3H MAT 19W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	979422	Dimensions (H/W/T/S) [mm]:	221/221/51
EAN:	5905963979422	Mounting dimensions [mm]:	200
Light source:	LED module	Impact resistance:	IK07
Rated power of the luminaire [W]:	19	Ingress protection:	IP65/IP20
Luminous flux [lm]:	2000	Mounting version:	recessed
Supply voltage [V]:	220-240	Working temperature [°C]:	from 0 to +25
Frequency [Hz]:	50-60	Emergency lighting [h]:	3
Luminous efficacy [lm/W]:	106	Number on the palette [pcs]:	130
Energy efficiency class:	E	Net weight [kg]:	0.820
Electrical protection class:	I	Category type:	downlights
Colour temperature [K]:	3000	LED lifespan L80B20 [h]:	58000
Colour rendering index:	>80	LED lifespan L70B50 [h]:	92000
Beam angle [°]:	110	LED lifespan L90B10 [h]:	28000
Diffuser material:	PC	Warranty [years]:	2
Diffuser type:	MAT	CE certificate:	299/2023
Material of the body:	ABS	HACCP:	852/2004
Colour of the body:	white	Manual:	Download PDF

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 299/2023