

ALTEZZO L 150 K 4900LM 830 IP65 RAL7016 40W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	40
Luminous flux [lm]*:	4900
Luminous efficacy [lm/W]:	123
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	3000
Diffuser material:	PC
Dimensions (H/W/T/S) [mm]:	150/150/500

CHARACTERISTICS

The Altezzo L 150 K wall lamp completes the entire line of outdoor lighting from the Altezzo series. It is characterized by a classic, simple shape and good light and mechanical parameters. It is available with three light color temperatures 2700 K 3000 K and 4000 K.

APPLICATION

The sconce's high IP65 waterproofing and IK08 impact resistance allow it to be used outdoors. It will prove useful as lighting for facades and building surroundings. Together with other products of the Altezzo line, it will provide good, eye-friendly and safety-friendly lighting and design consistency in housing estates, parks and gardens.

ALTEZZO L 150 K 4900LM 830 IP65 RAL7016 40W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	984372	Mounting dimensions [mm]:	75x75 - 90x90
EAN:	5905963984372	Impact resistance:	IK08
Light source:	LED module	Ingress protection:	IP65
Rated power of the luminaire [W]:	40	Mounting version:	surface
Luminous flux [lm]:	4900	Working temperature [°C]:	od -30 do +50
Luminous efficacy [lm/W]:	123	Dimensions of single box [mm]:	155/155/505
Energy efficiency class:	D	Number on the palette [pcs]:	82
Electrical protection class:	I	Net weight [kg]:	3.200
Colour temperature [K]:	3000	Category type:	accent lighting
Color rendering index (Ra) >:	70	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Beam angle [°]:	110	Warranty [years]:	5
Light distribution type:	general	CE certificate:	181/2023
Diffuser material:	PC	Manual:	Download PDF
Material of the body:	aluminium	Environmental Product Declaration (EPD):	852/2025
Colour of the body:	RAL7016	Plik LDT:	Download
Dimensions (H/W/T/S) [mm]:	150/150/500		

Card creation date:16 December 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 181/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl