

# MESSAGGIO 701 MM 1900 LM 830 IP20 I CL. 18 W WHITE

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	575549
<b>Light source:</b>	LED module
<b>Rated power [W] - range:</b>	18
<b>Luminous flux of the luminaire [lm] - range:</b>	1900
<b>Supply voltage [V]:</b>	220 - 240
<b>Frequency [Hz]:</b>	50 - 60
<b>Electrical protection class:</b>	I
<b>Colour temperature [K]:</b>	3000
<b>Ingress protection:</b>	IP20
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes pendant lamps with a minimalist form. They can come in all RAL colors, including a multicolor version, where the outside of the housing and the inside of the lamp have different colors. In this way, Messaggio provides unlimited design possibilities.

Thanks to the possibility of adjusting the length of the pendants from the Messaggio lamps, surprising light compositions can be created. Versions with DALI control allow you to change the value of the light output, which further enhances the decorative effect. The milky lampshade is made of PC, while the housing is made of solid yet visually delicate steel, which ensures the durability of the product.

## APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

# MESSAGGIO 701 MM 1900 LM 830 IP20 I CL. 18 W WHITE

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	575549	<b>Diffuser type:</b>	OPAL
<b>Rated power [W] - range:</b>	18	<b>Colour of the body:</b>	white
<b>EAN:</b>	5905963575549	<b>Diffuser colour:</b>	milky
<b>Luminous flux of the luminaire [lm] - range:</b>	1900	<b>Material of the body:</b>	Steel
<b>Light source:</b>	LED module	<b>Dimensions (H/W/T/S) [mm]:</b>	1230/701/80
<b>Supply voltage [V]:</b>	220 - 240	<b>Mounting dimensions [mm]:</b>	340
<b>Frequency [Hz]:</b>	50 - 60	<b>Ingress protection:</b>	IP20
<b>Colour temperature [K]:</b>	3000	<b>Mounting version:</b>	suspended
<b>Luminous efficacy [lm/W]:</b>	106	<b>Working temperature [°C]:</b>	from -25 to +35
<b>Electrical protection class:</b>	I	<b>Diode PCB material:</b>	aluminium
<b>SDCM:</b>	≤ 3	<b>Net weight [kg]:</b>	2.370
<b>LED lifespan L70B50 [h]:</b>	99000	<b>Warranty [years]:</b>	5
<b>LED lifespan L80B20 [h]:</b>	63000	<b>Category type:</b>	architectural
<b>LED lifespan L90B10 [h]:</b>	31000	<b>CE certificate:</b>	<a href="#">207/2023</a>
<b>Beam angle [°]:</b>	116 x 58	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Light distribution type:</b>	open space	<b>Plik LDT:</b>	
<b>Diffuser material:</b>	PC		

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 207/2023