

PORTAL EMERGENCY 250LM 20M AT IP54 1H+ SET OF 6 PICTOGRAMS

DETAILED CARD



TECHNICAL PARAMETERS

Index:	736704
Ingress protection:	IP54
Nominal power [W]:	3
Luminous flux [lm]*:	250
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	G
Diffuser material:	PC
Diffuser type:	clear

CHARACTERISTICS

Emergency Portal is a luminaire designed to illuminate open spaces and to indicate the direction of evacuation through the use of pictograms. A modern emergency module with an automatic test ensures maintenance-free reporting of errors or the need to replace the battery. Efficient LEDs of the latest generation ensure adequate illumination of escape routes.

APPLICATION

The high level of protection IP54 allows for use in industrial spaces, and the slender, timeless and neutral body of the luminaire will also be perfect for public facilities - offices, restaurants, commercial facilities. The possibility of ceiling and wall mounting extends the range of possible applications.

PORTAL EMERGENCY 250LM 20M AT IP54 1H+ SET OF 6 PICTOGRAMS

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	736704	Diffuser type:	clear
EAN:	5905963736704	Diffuser colour:	transparent
Light source:	LED module	Optics material:	ABS
Nominal power [W]:	3	Optics:	PC
Rated power of the luminaire [W]:	3	Colour of the body:	white
Supply voltage [V]:	3	Dimensions (H/W/T/S) [mm]:	280/185/55
Frequency [Hz]:	50-60	Ingress protection:	IP54
Luminous flux [lm]:	250	Mounting version:	surface
Luminous efficacy [lm/W]:	88	Working temperature [°C]:	from 0 to +35
Energy efficiency class:	G	Beam angle adjustment [°]:	no
Electrical protection class:	II	Net weight [kg]:	0.730
Colour temperature [K]:	4000	Category type:	emergency lighting
Colour rendering index:	>80	AC voltage range [V]:	207-253
SDCM:	≤ 3	Emergency lighting [h]:	1
Power factor:	0.90	Autotest:	yes
LED lifespan L70B50 [h]:	100000	CE certificate:	50/2023
Beam angle [°]:	120	Manual:	Download PDF
Diffuser material:	PC	CNBOP certificate:	5147/2023

Card creation date: 10 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 50/2023