

INDO LED EVO P DALI 3450LM PLX 830 (34W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	380945
Ingress protection:	IP20
Nominal power [W]:	34
Luminous flux [lm]*:	3450
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	powder coated steel
Diffuser material:	PMMA
Diffuser type:	OPAL

CHARACTERISTICS

Recessed mounted square luminaire with an integrated energy-saving LED light source. Powder-coated steel body. The lens diffuser is made of metal sheet and opalized PMMA. It provides comfortable and soft light.

APPLICATION

A versatile indoor luminaire designed for office rooms and areas of general public use. Suitable as a general light source for all sorts of work that require optical focus. Dedicated for new applications and as a replacement of traditional T8 and T5 tube luminaires with energy-saving LED lamps


INDO LED EVO P DALI 3450LM PLX 830 (34W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	380945	Material of the body:	powder coated steel
Light source:	LED module	Colour of the body:	white
Nominal power [W]:	34	Dimensions (H/W/T/S) [mm]:	106/595/595
Rated power of the luminaire [W]:	36.80	Impact resistance:	IK07
Supply voltage [V]:	220-240	Ingress protection:	IP20
Frequency [Hz]:	50 - 60	Mounting version:	recessed
Luminous flux [lm]:	3450	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	93	EAN:	5905963380952
Energy efficiency class:	E	Category type:	louvres
Electrical protection class:	I	AC voltage range [V]:	198 – 264
Colour temperature [K]:	3000	ETIM class:	EC002892
Colour rendering index:	>80	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.96	Manual:	Download PDF
LED lifespan L70B50 [h]:	50 000	DIMM DALI:	yes
Diffuser material:	PMMA	CE certificate:	77/2018
Diffuser type:	OPAL		

LIGHT CURVES



INDO LED EVO P DALI 3450LM PLX 830 (34W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white



Plasterboard recessing kit 630x630 white (999543)

Card creation date: 25 January 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 77/2018