

TAURUS MULTIBATTERY LED

DETAILED CARD



TECHNICAL PARAMETERS

Index:	256882
Ingress protection:	IP65
Impact resistance:	IK08
Colour temperature [K] - range:	2700 - 6500
Luminous flux [lm]*:	5000
Supply voltage [V]:	18
Electrical protection class:	III
Material of the body:	PP
Colour of the body:	green
Diffuser type:	milky

CHARACTERISTICS

Compact LED floodlight for professional use. Provides even and stable directional illumination. Made from impact-resistant polypropylene (PP). Smaller size and compact design make it more convenient to transport. Equipped with an on/off switch with 4-stage luminous flux adjustment. An additional button allows adjustment of the light colour in the range: 2700K to 6500K. The lamp is compatible with 18V batteries from manufacturers such as Bosch (18V Professional), Milwaukee, DeWalt, Metabo. The unit has a display showing the battery charge level.

Operating modes for battery operation:

for 5Ah Battery:

- 500 lm - operating time: 20h
- 1850 lm - operating time: 7h 15min
- 2750 lm - operating time: 4h 30min
- 4050 lm - operating time: 2h 15min

APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.

TAURUS MULTIBATTERY LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	256882	Impact resistance:	IK08
Light source:	LED module	Ingress protection:	IP65
Colour temperature [K] - range:	2700 - 6500	Net weight [kg]:	2.770
Luminous flux [lm]:	5000	Category type:	workplace floodlights
Supply voltage [V]:	18	LED lifespan L70B50 [h]:	140000
Electrical protection class:	III	LED lifespan L80B20 [h]:	85000
Colour rendering index:	>80	LED lifespan L90B10 [h]:	42000
Additional accessories:	Adapter for Bosch 18V. Milwaukee 18V, DeWalt 18V, Makita 18V and Metabo 18V batteries.	Light distribution type:	lamertian
SDCM:	≤ 3	ETIM class:	EC000346
Dimensions (H/W/T/S) [mm]:	280/280/148	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Beam angle [°]:	120	Warranty [years]:	2
Diffuser type:	milky	CE certificate:	77/2024
Material of the body:	PP	Manual:	Download PDF
Colour of the body:	green		

Card creation date: 15 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 77/2024