

OCULUS LED S ECO BLACK RAL9005 245X143MM 23000LM 840 I CL, IP65 120D (150W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	744716
Ingress protection:	IP65
Impact resistance:	IK08
Rated power of the luminaire [W]*:	150
Luminous flux [lm]*:	23000
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	C

CHARACTERISTICS

The Oculus LED S ECO is a HIGH-BAY luminaire made using LED technology. After the Oculus LED XS ECO, it is the smallest representative of the renowned OCULUS LED series, with dimensions optimised for maximum power obtained from a body made of die-cast aluminium, powder-coated in black or grey. The passive cooling system and the isolated power supply (black) have a positive effect on the thermal management of the lamp, its service life and the maintenance of the highest performance. LED modules with high luminous efficacy (up to 160 lm/W) ensure that the required lighting levels are achieved while saving energy and reducing purchasing costs. The diffuser is made of tempered glass, which does not alter the optics of the light source - providing a general distribution of 120 degrees. The lamp is terminated with electrical cables (which require an airtight connector if the connection is to be IP65 tight). The design of the lamp is suitable for pendant mounting using the threaded, eyebolt hook supplied. The lamp should be suspended using a cord or chain dedicated to such solutions (not supplied).

APPLICATION

The luminaire is designed for suspended mounting (using chains, cables, etc.) indoors, even in high humidity (IP65). It is ideal for factories and production halls as well as large warehouses and logistics centres.


OCULUS LED S ECO BLACK RAL9005 245X143MM 23000LM 840 I CL, IP65 120D (150W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	150	Colour of the body:	black
Index:	744716	Material of the body:	aluminium
Colour temperature [K]:	4000	Working temperature [°C]:	from -20 to +35
EAN:	5905963744716	Dimensions (H/W/T/S) [mm]:	143/245/245
Luminous flux [lm]:	23000	Impact resistance:	IK08
Light source:	LED	Ingress protection:	IP65
Colour rendering index:	>80	LED lifespan L70B50 [h]:	150000
Supply voltage [V]:	220-240	LED lifespan L80B20 [h]:	94000
Frequency [Hz]:	50-60	LED lifespan L90B10 [h]:	43000
Luminous efficacy [lm/W]:	154	Number on the palette [pcs]:	84
Energy efficiency class:	C	Net weight [kg]:	2.400
Electrical protection class:	I	Light distribution type:	symmetric
SDCM:	≤ 3	Remarks:	RAL9005
Beam angle [°]:	120	Warranty [years]:	5
Surge protection [kV]:	1	CE certificate:	82/2024
Diffuser material:	glass	Manual:	Download PDF

LIGHT CURVES



Card creation date: 19 September 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 82/2024