

SPARK LONG LED

DETAILED CARD



TECHNICAL PARAMETERS

Index:	607653
EAN:	5905963607653
Light source:	LED
Ingress protection:	IP44
Luminous flux of the luminaire [lm] - range:	190 - 920
Supply voltage [V]:	3.7
Electrical protection class:	III
Color rendering index (Ra) >:	80
Charging time [h:min]:	3
Battery life [h:min]:	1.4-11

CHARACTERISTICS

This work light is the perfect solution for mechanics, tradespeople and DIY enthusiasts. It is a modern work light that allows you to direct the beam in various directions (thanks to its swivel head). The lamp is designed to illuminate the work area. It is particularly useful in garages servicing cars, vans and lorries. The replaceable battery can be charged separately (away from the lamp) using a C-type connector.

APPLICATION

Car repair shops (repairs for cars, vans and lorries), car detailing centres, car washes, mobile repair services, etc.

SPARK LONG LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	607653	Diffuser type:	transparent
EAN:	5905963607653	Colour of the body:	black
Light source:	LED	Dimensions (H/W/T/S) [mm]:	350/70/50
Luminous flux of the luminaire [lm] - range:	190 - 920	Ingress protection:	IP44
Supply voltage [V]:	3.7	Working temperature [°C]:	from -20 to +35
Electrical protection class:	III	Switch:	yes
Color rendering index (Ra) >:	80	Magnet:	yes
Charging time [h:min]:	3	Net weight [kg]:	0.400
Battery life [h:min]:	1.4-11	Accessories included:	1 x 2600mAh 3.7V Li-Ion battery with a Type-C charging port – the battery can be charged separately from the lamp
Battery:	Li-Ion 3,7V	CE certificate:	66/2026
Battery capacity [mAh]:	2600	Manual:	Download PDF

SPARK LONG LED

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
607660	External charger for Li-ion batteries: 3.7V / 2600 mAh (SPARK LED lamp range)
607677	Replaceable Li-ion battery: 3.7V / 2600 mAh (SPARK LED lamp range)

Card creation date: 08 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 66/2026



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl