

DLN 220 LED EVO LV 220MM 1900LM 840 PRM (15W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	554384
Ingress protection:	IP65
Nominal power [W]:	15
Luminous flux [lm]*:	1900
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	D
Material of the body:	powder coated steel
Colour of the body:	grey
Diffuser material:	PC

CHARACTERISTICS

Surface mounted downlight with an integrated energy-saving LED GO! panel, with high ingress protection class IP65 and high impact protection class IK08. Opal diffuser made of polycarbonate ensures even light distribution.

APPLICATION

The fitting is intended for surface mounting. High ingress protection class IP65 and high impact protection class make it suitable for outdoor use. Small parameters and timeless design will also prove useful in offices, passageways and administrative buildings.

DLN 220 LED EVO LV 220MM 1900LM 840 PRM (15W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	ø220/140
Nominal power [W]:	15	Mounting dimensions [mm]:	ø90
Rated power of the luminaire [W]:	16.20	Impact resistance:	IK08
Supply voltage [V]:	220-240	Ingress protection:	IP65
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [lm]:	1900	Working temperature [°C]:	from -15 to +35
Luminous efficacy [lm/W]:	117	Net weight [kg]:	1.710
Energy efficiency class:	D	Gross weight [kg]:	2.550
Electrical protection class:	I	Index:	554384
Colour temperature [K]:	4000	EAN:	5905963554384
Colour rendering index:	>80	Category type:	downlights
SDCM:	≤ 3	Luminaire rated power O_{min} [W]:	16.80
Power factor:	0.92	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L70B50 [h]:	117000	Warranty [years]:	5
Beam angle [°]:	120	LED lifespan L80B20 [h]:	73000
Diffuser material:	PC	LED lifespan L90B10 [h]:	34000
Diffuser type:	PRM	CE certificate:	333/2023
Diffuser colour:	transparent	Warranty [years]:	5
Material of the body:	powder coated steel	Manual:	Download PDF
Colour of the body:	grey		

Card creation date: 30 April 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 333/2023