

POXAR SN-F LED

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|-----------------------------------|---------------|
| Index: | 324543 |
| Ingress protection: | IP40 |
| Nominal power [W]: | 1 |
| Material of the body: | PC |
| Diffuser material: | PMMA |
| Emergency lighting [h]: | 3 |
| Working temperature [°C]: | from 0 to +35 |
| Mounting version: | surface |
| Dimensions (H/W/T/S) [mm]: | 299/206/43 |

CHARACTERISTICS

Surface mounted emergency fitting with a power of 1W, available in maintained and non-maintained versions. The body is made of polycarbonate; PMMA mounting board. NiCd battery with manual testing function included, battery life in the event of emergency is 3h. NiCd battery life in the event of emergency is 3h. A bracket for wall mounting available on request.

APPLICATION

The main task of the independent emergency light fitting is to indicate the direction of evacuation routes and emergency exits after a power outage, i.e. in Safe Mode. Suitable for wall or ceiling mounting. Especially recommended in for technical rooms (corridors, stairways, garages, basements) where permanent emergency lighting is required.

POXAR SN-F LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-------------------------------------|------------|----------------------------------|---|
| Nominal power [W]: | 1 | Mounting version: | surface |
| Light source: | LED module | Working temperature [°C]: | from 0 to +35 |
| Emergency lighting [h]: | 3 | Net weight [kg]: | 0.850 |
| Supply voltage [V]: | 220-240 | CE certificate: | 68/2020 |
| Frequency [Hz]: | 50 - 60 | Warranty [years]: | 2 / 0.5 (bateria) |
| Electrical protection class: | II | Index: | 324543 |
| LED lifespan L70B50 [h]: | 50000 | EAN: | 5905963324543 |
| Beam angle [°]: | 120 | Category type: | emergency lighting |
| Diffuser material: | PMMA | ETIM class: | EC002892 |
| Material of the body: | PC | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Dimensions (H/W/T/S) [mm]: | 299/206/43 | Manual: | Download PDF |
| Ingress protection: | IP40 | | |

Card creation date: 06 December 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 68/2020