

DIONE LED PLUS 2350 LM 830 IP65 RCR OPAL WHITE 22W

BULKHEADS

LED



220-240 V
50-60 Hz

LED



IP65

IK10

TECHNICAL PARAMETERS

Index:	950407
Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W]:	22
Luminous flux [lm]*:	2350
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	A+
Material of the body:	ABS
Ring material:	ABS

*Tolerance +/- 10%

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED GO! panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Its base and ring are made of UV-resistant material. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

The fitting is offered in RCR version:

- sensor used to detect motion; for detection uses microwaves (active sensor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS 2350 LM 830 IP65 RCR OPAL WHITE 22W

BULKHEADS

LED

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ingress protection:	IP65
Nominal power [W]:	22	Mounting version:	surface
Rated power of the luminaire [W]:	24	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Motion sensor:	yes
Frequency [Hz]:	50 - 60	Dimensions of single box [mm]:	340/340/115
Luminous flux [lm]:	2350	Net weight of the luminaire [kg]:	1.220
Luminous efficacy [lm/W]:	97	Gross weight of the luminaire [kg]:	1.400
Energy efficiency class:	A+	Permeability factor of the diffuser:	0.73
Electrical protection class:	I	Index:	950407
Colour temperature [K]:	3000	EAN:	5905963950407
Colour rendering index:	>80	Category type:	bulkheads
SDCM:	≤ 3	AC voltage range [V]:	220 - 240
Power factor:	0.90	LED lifespan L70B50 [h]:	110000
Max load [RCR] [W]:	400	LED lifespan L80B20 [h]:	84000
Beam angle [°]:	120	LED lifespan L90B10 [h]:	33000
Diffuser material:	PC	Light distribution type:	open space
Diffuser type:	OPAL	CE certificate:	168/2019
Diffuser colour:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	ABS		
Colour of the body:	white		
Ring material:	ABS		
Ring colour:	white		
Dimensions [mm]:	ø340/115		
Mounting dimensions [mm]:	140		
Impact resistance:	IK10		

*Tolerance+/- 10%

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2020-07-21



Lena Lighting S.A.
ul. Kórnicka 52
63-000 Środa Wielkopolska

tel. +48 61 28 60 300
e-mail: office@lenalighting.pl
www.lenalighting.pl



The luminaire complies with the EU RoHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).



168/2019