

MADERA ALTUS LED EVO 900X900MM 8000LM PLX II IP41 WHITE 830 (88W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|-----------------------------------|-------------|
| Index: | 703898 |
| Ingress protection: | IP41 |
| Nominal power [W]: | 88 |
| Luminous flux [lm]*: | 8000 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | F |
| Colour of the body: | white |
| Dimensions (H/W/T/S) [mm]: | 900/900/120 |

CHARACTERISTICS

Suspended, square LED fitting with very high luminous flux, made of steel sheet, powder-coated grey, white, black. equipped with energy-saving light source LED-GO!. Opal PMMA diffuser ensures even light distribution and no glare effect.

APPLICATION

Suspended luminaire intended for indoor use in offices or common rooms. Suitable as a general light source in representative rooms.

MADERA ALTUS LED EVO 900X900MM 8000LM PLX II IP41 WHITE 830 (88W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-------------------------------------|-------------|--|---|
| Index: | 703898 | Ingress protection: | IP41 |
| Nominal power [W]: | 88 | Net weight [kg]: | 20 |
| Luminous flux [lm]: | 8000 | Category type: | louvres |
| Energy efficiency class: | F | Luminaire rated power O_{min} [W]: | 88 |
| Electrical protection class: | II | ETIM class: | EC002892 |
| Colour temperature [K]: | 3000 | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Colour rendering index: | >80 | CE certificate: | 225/2023 |
| SDCM: | ≤ 3 | Warranty [years]: | 2 |
| Colour of the body: | white | Manual: | Download PDF |
| Dimensions (H/W/T/S) [mm]: | 900/900/120 | | |

Card creation date: 08 April 2019

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 225/2023