

# MADERA ALTUS LED EVO 900X900MM 8000LM PLX II IP41 GREY 830 (88W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	703904
<b>Ingress protection:</b>	IP41
<b>Nominal power [W]:</b>	88
<b>Luminous flux [lm]*:</b>	8000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	F
<b>Colour of the body:</b>	grey
<b>Dimensions (H/W/T/S) [mm]:</b>	900/900/120

## CHARACTERISTICS

Suspended, square LED fitting with very high luminous flux, made of steel sheet, powder-coated grey, white, black. equipped with energy-saving light source LED-GO!. Opal PMMA diffuser ensures even light distribution and no glare effect.

## APPLICATION

Suspended luminaire intended for indoor use in offices or common rooms. Suitable as a general light source in representative rooms.

# MADERA ALTUS LED EVO 900X900MM 8000LM PLX II IP41 GREY 830 (88W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	703904	<b>Ingress protection:</b>	IP41
<b>Nominal power [W]:</b>	88	<b>Net weight [kg]:</b>	20
<b>Luminous flux [lm]:</b>	8000	<b>Category type:</b>	louvres
<b>Energy efficiency class:</b>	F	<b>Luminaire rated power <math>P_{\text{omin}}</math> [W]:</b>	88
<b>Electrical protection class:</b>	II	<b>ETIM class:</b>	EC002892
<b>Colour temperature [K]:</b>	3000	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Colour rendering index:</b>	>80	<b>CE certificate:</b>	<a href="#">225/2023</a>
<b>SDCM:</b>	≤ 3	<b>Warranty [years]:</b>	2
<b>Colour of the body:</b>	grey	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Dimensions (H/W/T/S) [mm]:</b>	900/900/120		

Card creation date: 08 April 2019

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 225/2023