

DEIMOS LED PLUS 400MM 1500 LM I KL. IP40 840 BLACK (12W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|--------|
| Index: | 073748 |
| Ingress protection: | IP40 |
| Nominal power [W]: | 12 |
| Luminous flux [lm]*: | 1500 |
| Colour temperature [K]: | 4000 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | E |
| Material of the body: | HIPS |
| Diffuser material: | PMMA |
| Diffuser type: | OPAL |

CHARACTERISTICS

Surface mounted, round LED fitting with very high diffuser diameter, high luminous flux and even light distribution. Includes an integrated energy-saving light source LED GO!. HIPS base, powder coated white and black; light, white diffuser made using termoforming method. Simple pawl-based mounting system does not require any additional tools. The luminaire may be used to replace standard four-lamp fittings in irregular shaped rooms.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- radio motion sensor,
- corridor function,
- DALI,
- emergency module.

APPLICATION

Surface mounted fitting intended for indoor use characterized by even light distribution and good surface lighting. Particularly suitable as a general light source in representative rooms and passageways. Thanks to exceptional lighting parameters, possible integration with the DALI system and decorative qualities, the product will surely prove its worth in large conference halls.


DEIMOS LED PLUS 400MM 1500 LM I KL. IP40 840 BLACK (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|--------------------------------------|---|
| Light source: | LED module | Ingress protection: | IP40 |
| Nominal power [W]: | 12 | Mounting version: | surface |
| Rated power of the luminaire [W]: | 13.90 | Working temperature [°C]: | from -20 to +35 |
| Supply voltage [V]: | 220-240 | Accessories included: | mounting pins 4 pcs |
| Frequency [Hz]: | 50 - 60 | Dimensions of single box [mm]: | 445/445/100 |
| Luminous flux [lm]: | 1500 | Net weight [kg]: | 1.300 |
| Luminous efficacy [lm/W]: | 108 | Gross weight [kg]: | 1.650 |
| Energy efficiency class: | E | Warranty [years]: | 5 |
| Electrical protection class: | I | CE certificate: | 390/2023 |
| Colour temperature [K]: | 4000 | Index: | 073748 |
| Colour rendering index: | >80 | EAN: | 5905963073748 |
| SDCM: | ≤ 3 | Category type: | bulkheads |
| Power factor: | 0.96 | Luminaire rated power O_{min} [W]: | 14 |
| Beam angle [°]: | 131.6 | AC voltage range [V]: | 198 - 264 |
| Diffuser material: | PMMA | LED lifespan L70B50 [h]: | 120000 |
| Diffuser type: | OPAL | LED lifespan L80B20 [h]: | 78000 |
| Diffuser colour: | white | LED lifespan L90B10 [h]: | 39000 |
| Optics material: | PMMA | Light distribution type: | open space |
| Optics: | lens | ETIM class: | EC002892 |
| Material of the body: | HIPS | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Colour of the body: | black | Impact resistance: | IK02 |
| Dimensions (H/W/T/S) [mm]: | ∅400/100 | Manual: | Download PDF |
| Mounting dimensions [mm]: | 306/306 | | |

LIGHT CURVES



Card creation date: 10 June 2019

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 390/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl