

TRANGO LED FI 160 4050LM 857 IP66 I KL. 20ST. (40W) RAL 7037

DETAILED CARD



TECHNICAL PARAMETERS

Index:	959141
Ingress protection:	IP66
Impact resistance:	IK06
Rated power of the luminaire [W]*:	40
Luminous flux [lm]*:	4050
Colour temperature [K]:	5700
Energy efficiency class:	E
Material of the body:	aluminium
Diffuser material:	tempered glass
Diffuser type:	transparent

CHARACTERISTICS

Modern floodlight LED lamp for lighting of architectural structures. Made of die-cast aluminium and powder coated in grey. The integrated optical system is available in many variants and ensures a wide range of adaptations.

APPLICATION

The lamp is an excellent choice for external illumination of architectural structures, and it enhances their artistic values.

TRANGO LED FI 160 4050LM 857 IP66 I KL. 20ST. (40W) RAL 7037

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	40	Material of the body:	aluminium
Light source:	LED module	Colour of the body:	RAL7037
Colour temperature [K]:	5700	Mounting dimensions [mm]:	ø150/40
Rated power of the luminaire [W]:	40	Impact resistance:	IK06
Luminous flux [lm]:	4050	Ingress protection:	IP66
Supply voltage [V]:	220-240	Net weight [kg]:	2.600
Frequency [Hz]:	50 - 60	Warranty [years]:	2
Beam angle [°]:	20	Index:	959141
Dimensions (H/W/T/S) [mm]:	265/160/232	EAN:	5905963959141
Energy efficiency class:	E	Category type:	accent lighting
Electrical protection class:	I	AC voltage range [V]:	220 - 240
Diffuser material:	tempered glass	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser type:	transparent	Manual:	Download PDF
Optics material:	PMMA	Plik LDT:	Download
Optics:	lens		