MITRA LED 7050LM 4000K MAT IP66 I KL. DALI (62W)

DETAILED CARD





LED fitting with high luminous efficiency and an energy-saving, integrated LED panel. Body made of polypropylene (PP) with glass fiber (GF), aluminum handle and polycarbonate diffuser (PC).

The lamp is available in two versions of light distribiution:

- general G1 with a frozen diffuser,
- road RM1 with a transparent diffuser and directional lens matrices made of PMMA.

IP66 ingress protection class and IK07 impact-rating features make this fitting shock-resistant (vandal-resistant). The integrated handle allows for top mounting to the pole. Colour of the body: gray (RAL 7010).

Standard equipped with:

- surge protection (SP10kV),
- H07RN-F cable with a length of 0.6 m and an IP66 quick connection.

APPLICATION

Fitting used in open spaces to lighten: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and mounting: post-top mounting. Mounting grip integrated with the fitting.

TECHNICAL PARAMETERS

Light source:	LED module
Ingress protection:	IP66
Nominal power [W]:	62
Luminous flux [lm]*:	7050
Colour temperature [K]:	4000
SDCM:	≤ 3
Colour rendering index:	80
Electrical protection class:	1
Energy efficiency class:	Е
Material of the body:	PP+FG



MITRA LED 7050LM 4000K MAT IP66 I KL. DALI (62W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	956546
EAN:	5905963956546
Light source:	LED module
Nominal power [W]:	62
Rated power of the luminaire [W]:	61.50
Supply voltage [V]:	220-240
Luminous flux [Im]:	7050
Luminous efficacy [lm/W]:	117
Energy efficiency class:	E
Electrical protection class:	1
Colour temperature [K]:	4000
Colour rendering index:	80
SDCM:	≤3
Power factor:	0.99
LED lifespan L70B50 [h]:	90000
Surge protection [kV]:	4
Diffuser material:	PC
Diffuser type:	frozen
Diffuser colour:	transparent
Material of the body:	PP+FG
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	398/398/175

Mounting dimensions [mm]:	Ø60
Ingress protection:	IP66
Mounting version:	on the pole
Working temperature [°C]:	from -15 to +35
Diode size [mm]:	2835
Dimensions of single box [mm]:	400/400/175
Net weight [kg]:	1.900
Warranty [years]:	5
Category type:	Park and city lighting
Light distribution type:	G1
Category of application:	parkings and bicycle paths
DIMM 1-10V:	yes
DIMM DALI:	yes
Gross weight [kg]:	1.900
Permeability factor of the diffuser:	0.80
ETIM class:	EC000062
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
ULOR:	0%
Warranty [years]:	5
CE certificate:	100/2023
Manual:	Download PDF
Plik LDT:	Download

LIGHT CURVES





MITRA LED 7050LM 4000K MAT IP66 I KL. DALI (62W)

DETAILED CARD

TECHNICAL DETAILS





MITRA LED

MITRA LED

